

ARCHITECTURAL SYMBOLS

BUILDING SECTION DETAIL NUMBER: 1, SHEET WHERE DETAIL IS DRAWN: A101

WALL SECTION DETAIL NUMBER: 1, SHEET WHERE DETAIL IS DRAWN: A101

INTERIOR ELEVATION ELEVATION NUMBER: A3.1, SHEET WHERE ELEVATION IS DRAWN: Ref

EXTERIOR ELEVATION SHEET WHERE DETAIL IS DRAWN: 1, SHEET WHERE ELEVATION IS DRAWN: A3.1

REVISION NUMBER 1

REVISION CLOUD

VIEW REFERENCE 1/A2.51, 17/A2.52

MATCHLINE

WINDOW / LOUVER TYPE W

Room name 101 → ROOM NUMBER

WALL TYPE A

SIGNAGE TYPE XXX

DOOR NUMBER 101

GLAZING TYPE A

DATUM ELEVATION

KEYNOTE NUMBER ?

TYP. RIGHT

TYP. LEFT

WALL

TRUE NORTH PROJECT TRUE NORTH, PROJECT NORTH

SHEETNOTE NUMBER ?

REGULATORY REQUIREMENTS

- PARTIAL LIST OF APPLICABLE CODES AS OF JANUARY 1, 2023***
- 2022 CALIFORNIA ADMINISTRATIVE CODE (CAC), PART 1, TITLE 24 CCR*
 - 2022 CALIFORNIA BUILDING CODE (CBC), PART 2, TITLE 24 CCR (2021 INTERNATIONAL BUILDING CODE, VOL. 1 & 2, AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA ELECTRICAL CODE (CEC), PART 3, TITLE 24 CCR (2020 NATIONAL ELECTRICAL CODE AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA MECHANICAL CODE (CMC), PART 4, TITLE 24 CCR (2021 IAPMO UNIFORM MECHANICAL CODE AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA PLUMBING CODE (CPC), PART 5, TITLE 24 CCR (2021 IAPMO UNIFORM PLUMBING CODE AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA ENERGY CODE (CEC), PART 6, TITLE 24 CCR
 - 2022 CALIFORNIA FIRE CODE (CFC), PART 9, TITLE 24 CCR (2021 INTERNATIONAL FIRE CODE AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA EXISTING BUILDING CODE (CEBC), PART 10, TITLE 24 CCR (2021 INTERNATIONAL EXISTING BUILDING CODE AND 2022 CALIFORNIA AMENDMENTS)
 - 2022 CALIFORNIA GREEN BUILDING STANDARDS CODE (CALGREEN), PART 11, TITLE 24 CCR
 - 2022 CALIFORNIA REFERENCED STANDARDS CODE, PART 12, TITLE 24 CCR
 - TITLE 19 CCR, PUBLIC SAFETY, STATE FIRE MARSHAL REGULATIONS
 - 2019 ASME A17.1/CSA B44-16 SAFETY CODE FOR ELEVATORS AND ESCALATORS (PER 2019 CBC PART 2 CH 35 NOTE: CAL/OSHA ELEVATOR UNIT ENFORCES CCR TITLE 8 AND USES THE 2004 ASME A17.1 BY ADOPTION.

- PARTIAL LIST OF APPLICABLE STANDARDS**
- NFPA 13 STANDARD FOR THE INSTALLATION OF SPRINKLER SYSTEMS (CA AMENDED) 2016 EDITION
 - NFPA 14 STANDARD FOR THE INSTALLATION OF STANDPIPE AND HOSE SYSTEMS (CA AMENDED) 2016 EDITION
 - NFPA 17 STANDARD FOR DRY CHEMICAL EXTINGUISHING SYSTEMS, 2017 EDITION
 - NFPA 17A STANDARD FOR WET CHEMICAL EXTINGUISHING SYSTEMS, 2017 EDITION
 - NFPA 20 STANDARD FOR THE INSTALLATION OF STATIONARY PUMPS FOR FIRE PROTECTION 2016 EDITION
 - NFPA 22 STANDARD FOR WATER TANKS FOR PRIVATE FIRE PROTECTION, 2013 EDITION
 - NFPA 24 STANDARD FOR THE INSTALLATION OF PRIVATE FIRE SERVICE MAINS AND THEIR APPURTENANCE, 2016 EDITION
 - NFPA 72 - NATIONAL FIRE ALARM AND SIGNALING CODE (CA AMENDED), 2016 EDITION
 - NFPA 80 - STANDARD FOR FIRE DOORS AND OTHER OPENING PROTECTIVES, 2016 EDITION
 - NFPA 2001 - STANDARD ON CLEAN AGENT FIRE EXTINGUISHING SYSTEMS, 2015 EDITION
 - UL 300 - STANDARD FOR FIRE TESTING OF FIRE EXTINGUISHING SYSTEMS FOR PROTECTION OF COMMERCIAL COOKING EQUIPMENT, 2005 (R2010)
 - UL 464 - AUDIBLE SIGNALING DEVICES FOR FIRE ALARM AND SIGNALING SYSTEMS, INCLUDING ACCESSORIES, 2016 EDITION
 - UL 521 - STANDARD FOR HEAT DETECTORS FOR FIRE PROTECTIVE SIGNALING SYSTEMS, 1999 EDITION

- QUALITY ASSURANCE**
- THE PROJECT FALLS UNDER THE JURISDICTION OF THE DEPARTMENT OF THE STATE ARCHITECT (DSA), STATE OF CALIFORNIA.
 - DSA WILL INSPECT THE WORK PERIODICALLY PURSUANT TO TITLE 24, PART 1, SECTION 4-334, CCR.
 - MATERIAL TESTING SHALL BE CONDUCTED PER TITLE 24, PART 1, SECTION 4-335.
 - ALL TESTING MUST BE DONE BY AN INDEPENDENT TESTING SERVICE EMPLOYED BY THE OWNER, AND APPROVED BY THE ARCHITECT.
 - THE OWNER SHALL PAY FOR ALL TESTING PER TITLE 24, PART 1, SECTION 335(C), CCR.
 - WHERE TEST RESULTS DO NOT MEET PROJECT REQUIREMENTS, THE CONTRACTOR SHALL BEAR ALL COSTS OF THE TESTING, INCLUDING REIMBURSEMENT OF THE TESTING FEES, TO THE OWNER.
 - SPECIAL INSPECTIONS, WHERE REQUIRED, WILL BE PERFORMED PER TITLE 24, PART 1, SECTION 4-333(C), CCR.

- PERMITS, FEES, AND NOTICES**
- PURSUANT TO THE GENERAL CONDITIONS, THE CONTRACTOR (OR THE SUBCONTRACTORS IT MAY ASSIGN) SHALL OBTAIN REQUIRED PERMITS FROM GOVERNING AUTHORITIES.
 - ANY REQUIREMENTS ISSUED WITH A PERMIT OR MARKED ON THE PERMIT SET OF CONSTRUCTION DOCUMENTS BY THE ISSUING AGENCY, AS CONDITIONS OF THE AGENCY'S PERMIT APPROVAL, SHALL BE REFERRED TO THE ARCHITECT FOR DIRECTION.

- REPORTS AND APPROVALS**
- VERIFIED REPORTS MUST BE FILED BY THE ARCHITECT, INSPECTOR, AND CONTRACTOR.
 - THE INSPECTOR SHALL FILE VERIFIED REPORTS PER TITLE 24, PART 1, SECTION 4-336.
 - THE ARCHITECT SHALL FILE VERIFIED REPORTS PER TITLE 24, PART 1, SECTION 4-336.
 - THE CONTRACTOR SHALL FILE VERIFIED REPORTS PER TITLE 24, PART 1, SECTION 4-336 AND 4-343(C).
 - IN ADDITION TO THE REQUIREMENTS OF THE GENERAL CONDITIONS, ALL ADDENDA AND CONSTRUCTION CHANGE DOCUMENTS REQUIRE DSA APPROVAL PURSUANT TO TITLE 24, PART 1, SECTION 4-338, CCR.
 - CONSTRUCTION CHANGE DOCUMENTS SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL.

- DUTIES OF THE ARCHITECT AND CONTRACTOR**
- THE FOLLOWING SHALL PERFORM THE DUTIES DESCRIBED:
 - THE ARCHITECT, PER TITLE 24, PART 1, SECTION 4-333(A) AND 4-341, CCR.
 - THE CONTRACTOR, PER TITLE 24, PART 1, SECTION 4-343, CCR. 2.

- OTHER REQUIREMENTS**
- A COPY OF PARTS 1 TO 5 TITLE 24, C.C.R. SHALL BE KEPT ON JOB SITE DURING CONSTRUCTION.
 - DSA SHALL BE NOTIFIED AT THE START OF CONSTRUCTION AND PRIOR TO THE PLACEMENT OF CONCRETE (SECTION 4-331), PART 1).
 - THE PROJECT INSPECTOR MUST BE EMPLOYED BY THE OWNER AND APPROVED BY THE ARCHITECT AND DSA. INSPECTION SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 4-333(b), PART 1, TITLE 24. THE DUTY OF THE INSPECTOR SHALL BE IN ACCORDANCE WITH SECTION 4-342, PART 1, TITLE 24.
 - DSA IS NOT SUBJECT TO ARBITRATION.
 - ANY SUBSTITUTION SHALL BE CONSIDERED A CHANGE TO THE APPROVED APPLICATION AND SHALL BE SUBJECT TO FURTHER REVIEW AND APPROVAL BY DSA PRIOR TO FABRICATION, CONSTRUCTION, OR USE. SUBSTITUTION OF MAJOR STRUCTURAL ELEMENTS SUCH AS FRAMING ETC. MUST BE STAMPED AND SIGNED BY THE ARCHITECT AND THE STRUCTURAL ENGINEER.
 - BUILDINGS SHALL BE GROUNDED TO THE SITE PER TITLE 24, CCR.
 - THE INTENT OF THE DRAWINGS AND SPECIFICATIONS IS TO CONSTRUCT THE SCHOOL BUILDING IN ACCORDANCE WITH TITLE 24, CCR. SHOULD ANY CONDITIONS DEVELOP NOT COVERED BY THE CONTRACT DOCUMENTS WHEREIN THE FINISHED WORK WILL NOT COMPLY WITH SAID TITLE 24, CCR, A CONSTRUCTION CHANGE DOCUMENT DETAILING AND SPECIFYING THE REQUIRED WORK SHALL BE SUBMITTED TO AND APPROVED BY DSA BEFORE PROCEEDING WITH THE WORK.

PROJECT NOTES

- ALL WORK SHALL CONFORM TO 2022 TITLE 24, CALIFORNIA CODE OF REGULATIONS (CCR).
- DRAWINGS AND SPECIFICATIONS REPRESENT FINISHED CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR THE MEANS AND METHODS OF CONSTRUCTION INCLUDING BUT NOT LIMITED TO SHORING AND TEMPORARY BRACING.
- THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS SHOWN ON THE DRAWINGS AND SHALL NOTIFY THE ARCHITECT OF ANY DISCREPANCIES.
- FIGURE DIMENSIONS SHALL TAKE PRECEDENCE OVER SCALED DIMENSIONS.
- VERIFY ALL ROUGH-IN DIMENSIONS FOR EQUIPMENT PROVIDED IN THIS CONTRACT OR EQUIPMENT BY OTHERS.
- REPETITIVE FEATURES ARE NOT DRAWN IN THEIR ENTIRETY AND SHALL BE COMPLETELY PROVIDED AS IF DRAWN IN FULL.
- ALL EXISTING WORK WHICH IS DAMAGED, CUT OR REMOVED DURING AND AS A RESULT OF WORK UNDER THIS CONTRACT, AND WHICH IS TO REMAIN IN THE COMPLETED WORK SHALL BE RESTORED. PRINCIPAL ITEMS INCLUDE THE PATCHING OF WORK CUT AS A RESULT OF THE INSTALLATION OF OR REPAIR TO MECHANICAL, PLUMBING AND ELECTRICAL SYSTEMS; AND DEMOLITION ASSOCIATED WITH REMODELING.
- CUTTING SHALL BE KEPT TO A MINIMUM. WHEREVER POSSIBLE UNDERLYING SUPPORT SYSTEMS SHALL BE LEFT INTACT. UNLESS NOTED OTHERWISE, NO CUTTING OF THE STRUCTURAL SYSTEM WILL BE ALLOWED WITHOUT PRIOR APPROVAL OF THE STRUCTURAL ENGINEER.
- THE EXACT EXTENT OF CUTTING AND PATCHING REQUIRED TO PERFORM WORK UNDER THIS CONTRACT SHALL BE DETERMINED BY THE CONTRACTOR. WHENEVER IT IS POSSIBLE TO VISUALLY DISTINGUISH THE PATCHWORK FROM SURROUNDING MATERIALS THE PATCH SHALL BE RECTANGULAR IN SHAPE OR MATCH A MODULAR UNIT IN MODULAR MATERIALS. PATCH ATTACHMENT HOLES FROM REMOVED ITEMS TO MATCH SURROUNDING SURFACE. PATCH SURFACES WHICH BECOME EXPOSED WHEN MOUNTED ITEMS ARE REMOVED. MAINTAIN FIRE RATING OF ASSEMBLIES. SEE SPECIFICATION SECTION 01045.
- DEMOLITION AND REMOVAL WORK INCLUDES REQUIRED CAPPING AND DISCONNECTION OF ABANDONED SERVICES.
- WHEN SUBSTITUTIONS OR REVISION OF EITHER A DETAIL OR AN ASSEMBLY SHOWN WITH A U/L, CBC, OR GA LISTING NUMBER IS PROPOSED BY THE CONTRACTOR, A SIMILAR OR EQUAL TESTING MUST BE SUBMITTED TO THE ARCHITECT FOR APPROVAL BY DSA.
- UNLESS OTHERWISE NOTED, PLAN DIMENSIONS ARE TO EITHER FACE OF (E) FINISH, FACE OF (N) STUDS, FACE OF CONCRETE AND CMU, OR CENTER LINE.
- PROVIDE AND VERIFY SIZE AND LOCATION OF THE FOLLOWING: REQUIRED ACCESS DOORS, OPENINGS, FURRRINGS, ANCHORS, INSERTS AND BLOCKING REQUIRED FOR ACCESSORIES, AND MECHANICAL AND ELECTRICAL EQUIPMENT.
- WHERE A DOOR IS LOCATED NEAR THE CORNER OF A ROOM, AND IS NOT LOCATED BY THE PLAN DIMENSION OR DETAIL, THE DIMENSION SHALL BE 4-INCH FROM THE FACE OF WALL TO THE FINISH DOOR OPENING.
- ALL NOTED ITEMS ARE TO BE PROVIDED NEW UNLESS NOTED AS EXISTING (E) OR OTHERWISE NOTED. REPLACE MEANS TO REMOVE EXISTING (E). IF NOT MISSING, AND PROVIDE NEW (N). U.O.N. SALVAGE. MEANS TO REMOVE INTACT, DELIVER OR STORE AND PROTECT FOR RE-USE AS INDICATED. DELIVER TO DISTRICT MEANS DELIVER TO A LOCATION ON THIS CAMPUS WHERE DIRECTED BY THE SCHOOL DISTRICT.
- HOLES IN WOOD FOR LAG SCREWS SHALL FIRST BE BORED TO THE SAME DIAMETER AND DEPTH AS THE SHANK. HOLES FOR THE THREADED PORTION SHALL BE BORED WITH A BIT NOT LARGER THAN THE BASE OF THE THREADS.
- GENERAL CONTRACTORS AND ALL SUBCONTRACTORS ARE STRONGLY ADVISED TO VERIFY EXISTING SITE CONDITIONS PRIOR TO BID. SEE "INSTRUCTION TO BIDDERS" FOR TIME OF PRE-BID JOB WALK.
- PAVED WALKS SHALL CONFORM TO SECTION 3325, TITLE 24.
- ANY WORK ON THE FIRE ALARM SYSTEM WHERE APPLICABLE, SHALL BE BID TO THE GENERAL CONTRACTOR BY A SUBCONTRACTOR SPECIALIZING IN AND LICENSED TO INSTALL OR PERFORM WORK ON FIRE ALARM SYSTEMS. THE WORK SHALL NOT TO BE BID AS A SUBCONTRACT TO THE ELECTRICAL CONTRACTOR.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY NECESSARY WORK TO MAINTAIN SERVICE ON THE EXISTING INTRUSION/BURGLAR ALARM SYSTEM, FIRE ALARM CIRCUITS, AND/OR ANY OTHER CIRCUITRY TO COMPLETE ANY OTHER TASK THAT IS PART OF THIS CONTRACT.
- ANY EXISTING EQUIPMENT INCLUDING BUT NOT LIMITED TO LOW VOLTAGE WIRING OR SYSTEM THAT IS DAMAGED OR LEADS TO ANY COMPONENT MALFUNCTION SHALL BE REPAIRED AT THE EXPENSE OF THE CONTRACTOR TO THE SATISFACTION OF THE SCHOOL DISTRICT. ALL EXISTING EQUIPMENT OR SYSTEMS ARE ASSUMED IN PROPER FUNCTIONING ORDER U.O.N. THE CONTRACTOR IS RESPONSIBLE FOR NOTIFYING THE SCHOOL DISTRICT OF ANY MALFUNCTIONING EQUIPMENT OR SYSTEMS PRIOR TO WORK IN THE AREA OF SCOPE OF WORK.
- EXISTING ELECTRICAL OUTLETS SHALL NOT BE REMOVED UNLESS REPLACED WITH LIKE KIND OUTLETS AT A SIMILAR LOCATION UNLESS APPROVED BY THE OWNER OR ARCHITECT.
- HAZARDOUS MATERIAL TESTING, IF APPLICABLE WILL BE PROVIDED BY THE SCHOOL DISTRICT.
- SUBSTITUTE MATERIALS AND SYSTEMS - SECTION 17(i) TITLE 21, GOVERNS AND READS IN PART: "THE ESTIMATED COST OF A PROJECT SHALL BE INCREASED AS NECESSARY TO INCLUDE THE ESTIMATED COST OF EVERY ALTERNATE BUILDING OR PORTION THEREOF SHOWN ON THE PLANS AND SPECIFICATIONS AS IF EACH ALTERNATE BUILDING AND PORTION WERE TO BE CONSTRUCTED SEPARATELY AND SIMULTANEOUSLY.
- SHOULD ANY CONDITIONS DEVELOP NOT COVERED BY THE CONTRACT DOCUMENTS, A CHANGE ORDER DETAILING AND SPECIFYING THE REQUIRED WORK SHALL BE SUBMITTED AND APPROVED BY DSA BEFORE PROCEEDING WITH THE WORK.
- ALL ADDENDA AND CONSTRUCTION CHANGE DOCUMENT REQUIRE DSA APPROVAL PRIOR TO START OF WORK PURSUANT TO THE CALIFORNIA CODE OF REGULATIONS, TITLE 24, PART 1, SECTION 4-338.
- THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS IS THAT THE WORK OF THE ALTERATION, REHABILITATION OR RECONSTRUCTION IS TO BE IN ACCORDANCE WITH TITLE 24, CALIFORNIA CODE OF REGULATIONS. SHOULD ANY EXISTING CONDITIONS SUCH AS DETERIORATION OR NONCOMPLYING CONSTRUCTION BE DISCOVERED WHICH IS NOT COVERED BY THE CONSTRUCTION DOCUMENTS WHEREIN THE FINISHED WORK WILL NOT COMPLY WITH TITLE 24, CALIFORNIA CODE OF REGULATIONS, A CONSTRUCTION CHANGE DOCUMENT, OR A SEPARATE SET OF PLANS AND SPECIFICATIONS DETAILING AND SPECIFYING THE REQUIRED WORK SHALL BE SUBMITTED AND APPROVED BY DSA BEFORE PROCEEDING WITH THE WORK.
- ALL REQUIRED WORK SHALL BE COMPLETED TO ENTIRETY.
- ALL EXISTING FINISHES DISTURBED AS A RESULT OF CONSTRUCTION SHALL BE RESTORED, PATCHED, RECONSTRUCTED AND/OR PAINTED TO MATCH EXISTING ADJACENT SURFACE. MATCH PAINTING SHALL BE EXTENDED TO NATURAL BREAKS IN MATERIAL.
- COMPLIANCE WITH CFO CHAPTER 33, FIRE SAFETY, SHALL BE ENFORCED DURING DEMOLITION AND CONSTRUCTION. CBC CHAPTER 33 SAFETY SHALL BE ENFORCED DURING CONSTRUCTION.
- CHANGES TO THE APPROVED DRAWINGS AND SPECIFICATIONS SHALL BE MADE BY AN ADDENDUM OR A CONSTRUCTION CHANGED DOCUMENT (CCD) APPROVED BY THE DIVISION OF THE STATE ARCHITECT, AS REQUIRED BY SECTION 4-338, PART 1, TITLE 24, CCR.
- A "DSA CERTIFIED" PROJECT INSPECTOR EMPLOYED BY THE DISTRICT (OWNER) SHALL CONDUCT ALL THE REQUIRED TESTS AND INSPECTIONS FOR THE PROJECT.
- A DSA ACCEPTED TESTING LABORATORY DIRECTLY EMPLOYED BY THE DISTRICT (OWNER) SHALL CONDUCT ALL THE REQUIRED TESTS AND INSPECTIONS FOR THE PROJECT.
- GRADING PLANS, DRAINAGE IMPROVEMENTS, ROAD AND ACCESS REQUIREMENTS AND ENVIRONMENTAL HEALTH CONSIDERATIONS SHALL COMPLY WITH ALL LOCAL ORDINANCES.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-120975 INC.
REVIEWED FOR
SS FLS ACS
DATE: 5/17/2023

HKIT ARCHITECTS
538 NINTH STREET SUITE 240 • OAKLAND, CA 94607
T 510 625 9800 • F 510 625 9801 • WWW.HKIT.COM

WAGNER RANCH ELEMENTARY SCHOOL RELOCATABLE PROJECT

350 CAMINO PABLO, ORINDA, CA 94563
JOB NO. 21010.03
DRAWN -
CHECKED -
JOB CAPTAIN -

ISSUE

△	DATE	DESCRIPTION
	05.04.23	DSA SUBMITTAL
	05.08.23	DSA BACKCHECK

DRAWING TITLE
PROJECT DATA

SCALE 1/4" = 1'-0"
G0.01
COPYRIGHT © 2016 HKIT ARCHITECTS

**WAGNER RANCH
 ELEMENTARY
 SCHOOL -
 PORTABLE**



350 CAMINO PABLO
 ORINDA, CA 94563
 JOB NO. 220055
 DRAWN SN
 CHECKED RB
 JOB CAPTAIN MR
 ISSUE 04/28/23

DATE	DESCRIPTION
1 05/04/23	DSA SUBMITTAL

DRAWING TITLE
**GRADING AND
 DRAINAGE PLAN**

SCALE As indicated

C1.0
 COPYRIGHT © 2016 HKIT ARCHITECTS



1 SITE PLAN


CONSTRUCTION NOTES:

- 1 REMOVE AND REPLACE CONCRETE SIDEWALK - SEE DETAIL (1) C2.1
- 2 DOWEL INTO EXISTING CONCRETE - SEE DETAIL (2) C2.1
- 3 INSTALL ISOLATION JOINT ALONG BUILDING COLUMNS AND OTHER STRUCTURES - SEE DETAIL (3) C2.1
- 4 CONFORM EXISTING AC PAVEMENT - SEE DETAIL (4) C2.1
- 5 INSTALL FEDERAL YELLOW TRUNCATED DOMES PER CALTRANS STANDARD - SEE DETAIL (5) C2.2
- 6 INSTALL CASE "A" CURB RAMP - SEE DETAIL (6) C2.2
- 7 CONSTRUCT VERTICAL CURB (TYP M1-6) - SEE DETAIL (7) C2.1
- 8 SIGN AND STRIPE PARKING STALLS PER CALTRANS PLAN A90A - SEE DETAIL (8) C2.2
- 9 CONSTRUCT CURB & GUTTER (TYPE S1-6) - SEE DETAIL (9) C2.1
- 10 CONFORM TO EXISTING CURB
- 11 INSTALL CASE "C" CURB RAMP - SEE DETAIL (11) C2.2


LEGEND

- ADA PATHWAY
- REMOVE AND REPLACE EXISTING CONCRETE PATHWAY IN COMPLIANCE WITH ADA REQUIREMENTS
- REMOVE AND REPLACE EXISTING AC PAVING AND BASE - CONFORM TO EXISTING

△	DATE	DESCRIPTION
1	05/04/23	DSA SUBMITTAL




1 TYPICAL CONCRETE SIDEWALK
 SCALE: NTS




NOTE:
 AT LOCATIONS WHERE THE PROPOSED GRADE IS 0.1' OR MORE ABOVE THE EXISTING ASPHALT SURFACE THE CONTRACTOR CAN OVERLAY INSTEAD OF REPLACING THE WHOLE PAVEMENT SECTION

3 TIE-IN PAVEMENT/CONFORM
 SCALE: NTS




2 TYPICAL CONSTRUCTION JOINTS
 SCALE: NTS




5 TYPICAL CURB AND GUTTER
 SCALE: NTS



6 TYPICAL VERTICAL CURB
 SCALE: NTS







5 CONTRA COSTA COUNTY STD CURB DETAIL
 NTS









7 TYPICAL REINF BENDS, HOOKS AND OFFSETS
 SCALE: NTS

△	DATE	DESCRIPTION
1	05/04/23	DSA SUBMITTAL



- NOTES:**
- As site conditions dictate, Case A through Case G curb ramps may be used for corner installations similar to those shown in Detail A and Detail B. The case of curb ramps used in Detail A do not have to be the same. Case A through Case G curb ramps also may be used at mid block locations, as site conditions dictate. For specific site condition configuration, including the conform to existing sidewalk, see Project Plans.
 - If distance from curb to back of sidewalk is too short to accommodate ramp and 4'-2" platform (landing) as shown in Case A, the sidewalk may be depressed longitudinally as in Case B or C or may be widened as in Case D.
 - When ramp is located in center of curb return, crosswalk configuration must be similar to that shown for Detail B.
 - As site conditions dictate, the retaining curb side and the flared side of the Case G ramp shall be constructed in reversed position.
 - The ramp portion of the curb ramp is a typical rectangle, unless modified in the Project Plans.
 - Side slope of ramp flares vary uniformly from a maximum of 9.0% at curb to conform with longitudinal sidewalk slope adjacent to top of the ramp, except in Case C and Case F.
 - The adjacent surfaces of transitions at curb ramps to walks, gutters, and streets shall be at the same level.
 - Counter slopes of adjoining gutters and road surfaces immediately adjacent to and within 24 inches of the curb ramp shall not be steeper than 1:20H (5.0%). Gutter pan slope shall not exceed 1" of depth for each 2'-0" of width.
 - Transition gutter pan slope from 1" of depth for each 2'-0" of width to match typical gutter pan slope per Standard Plan A87A.
 - The detectable warning surface will be a rectangle as shown at back of curb, unless modified in the Project Plans. Curb ramps shall have a detectable warning surface that extends the full width and 3'-0" depth of the ramp. Detectable warning surfaces shall extend the full width of the ramp except a maximum gap of 1 inch is allowed on each side of the ramp. Detectable warning surfaces shall conform to the requirements in the Standard Specifications.
 - Sidewalk and ramp thickness, "T", shall be 3/2" minimum.
 - Utility pull boxes, manholes, vaults and all other utility facilities within the boundaries of the curb ramp will be relocated or adjusted to grade by the owner prior to, or in conjunction with, curb ramp construction.
 - Detectable warning surface may have to be cut to allow removal of utility covers while maintaining detectable warning width and depth.



LPG Fire Protection Inc. 1742 Seville Way, San Jose, CA 95131
Location: 8 Altamira Rd. Orinda, CA 94603

REQUEST FOR INFORMATION
RFI Number: [] Date Submitted: 4/23/2023 Cost Impact [] Schedule Impact []

Subject: Water Flow
Drawing / Spec Reference: [] Trade: Fire Protection System
Trade RFI #: []

Information Requested: Seeking the water flow calculation from Fire Hydrant Near Field

Response: Information is provided from the April 23, 2023 Annual Fire Hydrant Inspection Report:

No. of Office	Flow Tested	GPM Date	Flushed	Cond.	Year/Style	Static	Residual	Prst	Static	Restore	Hydrant
95	psi @ 1835	GPM			1980	Greenberg	100	110	95	100	

Reviewer(s): Luis Gregorio 4/23/2023
Date Returned: []

GENERAL NOTES

- A. SEE CIVIL AND ELECTRICAL DRAWINGS FOR RESPECTIVE SCOPE OF REMOVAL WORK.
- B. GENERAL CONTRACTOR RESPONSIBLE FOR LOCATING ALL UNDERGROUND UTILITY LINES AND COORDINATION WITH CONSTRUCTION PRIOR TO WORK.
- C. PROVIDE ANY AND ALL REMOVAL WORK NECESSARY TO ALLOW FOR INSTALLATION AND/OR CONSTRUCTION OF WORK TO BE PROVIDED.
- D. RESTORE, PATCH, REPAIR, REPLACE TO CONDITION PRIOR TO START OF CONSTRUCTION ANY EXISTING ITEM REMOVED OR OTHERWISE MODIFIED TO ALLOW FOR INSTALLATION OR CONSTRUCTION OF WORK TO BE PROVIDED.
- E. ALL FINISHES, INCLUDING BUT NOT LIMITED TO GROUND SURFACE, DISTURBED AS A RESULT OF CONSTRUCTION OR REMOVAL WORK SHALL BE RESTORED, PATCHED, REPAIRED, REPLACED, OR RECONSTRUCTED TO CONDITION PRIOR TO START OF CONSTRUCTION. FINISHED GROUND SURFACE TO MATCH EXISTING INCLUDING BUT NOT LIMITED TO GRADES/ELEVATIONS PRIOR TO START OF CONSTRUCTION. PREP AND PAINT ALL WORK PROVIDED THAT IS NOT FACTORY FINISHED. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE OF COLORS.
- F. SEE SIGNAGE SCHEDULE FOR SIGNAGE INFORMATION.
- G. PV ENERGY SYSTEMS WITH POWER OUTPUT AND BATTERY STORAGE ARE NOT REQUIRED FOR THIS PROJECT.

SITE PLAN LEGEND


AREA OF SCOPE OF WORK NO WORK THIS BUILDING
20'-0" WIDE EMERGENCY VEHICLE ACCESS ROUTE
INDICATES ACCESSIBLE PATH OF TRAVEL IS A BARRIER FREE ACCESS ROUTE WITHOUT ANY ABRUPT LEVEL CHANGES EXCEEDING 1/2" BEVELED AT 1:2 MAX. SLOPE OR VERTICAL LEVEL CHANGES NOT EXCEEDING 1/4" MAX. AND AT LEAST 48" WIDE. SURFACE IS SLIP RESISTANT, STABLE, FIRM AND SMOOTH. CROSS SLOPE DOES NOT EXCEED 2% AND SLOPE IN THE DIRECTION OF TRAVEL IS LESS THAN 5% UNLESS OTHERWISE INDICATED.
ARCHITECT TO VERIFY THAT ALL BARRIERS IN THE PATH OF TRAVEL HAVE BEEN REMOVED UNDER THIS PROJECT AND PATH OF TRAVEL COMPLIES WITH CBC 11B.
PROPERTY LINE ASSUMED PROPERTY LINE
(E) FIRE HYDRANT
B ACCESSIBLE BOY'S RESTROOM TO SERVE AREA OF WORK, SEE 3/A2.01
G ACCESSIBLE GIRL'S RESTROOM TO SERVE AREA OF WORK, SEE 2/A2.01
S ACCESSIBLE STAFF RESTROOM TO SERVE AREA OF WORK, SEE 1/A2.01
DF ACCESSIBLE DRINKING FOUNTAIN TO SERVE AREA OF WORK, SEE 2/A2.03

PARKING COUNT

(E) STAFF PARKING LOT 1 PARKING SPACES	20	ACCESSIBLE SPACES AT PARKING LOT 1 REQUIRED: 1 PROVIDED: 2 (1 VAN ACC.)
(E) VISITOR & STAFF PARKING LOT 2 PARKING SPACES	60	ACCESSIBLE SPACES AT PARKING LOT 2 REQUIRED: 3 PROVIDED: 3 (1 VAN ACC.)
TOTAL SPACES	80	

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-120975 INC.
REVIEWED FOR: []
DATE: 5/17/2023

HKITE ARCHITECTS
538 NINTH STREET SUITE 240 • OAKLAND, CA 94607
T 510 625 9800 • F 510 625 9801 • WWW.HKIT.COM



WAGNER RANCH ELEMENTARY SCHOOL SCOOTABLE PROJECT

350 CAMINO PABLO, ORINDA, CA 94603
JOB NO. 21010.03
DRAWN -
CHECKED -
JOB CAPTAIN -


ISSUE

DATE	DESCRIPTION
05.04.23	DSA SUBMITTAL
05.08.23	DSA BACKCHECK

DRAWING TITLE OVERALL SITE PLAN

SCALE As indicated

A1.00



DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE STATEMENT:
THE POT IDENTIFIED IN THESE CONSTRUCTION DOCUMENTS MEETS THE REQUIREMENTS OF THE CURRENT APPLICABLE CALIFORNIA BUILDING CODE (CBC) ACCESSIBILITY PROVISIONS FOR PATH OF TRAVEL REQUIREMENTS FOR ALTERATIONS, ADDITIONS AND STRUCTURAL REPAIRS.
AS PART OF THE DESIGN OF THIS PROJECT, THE POT WAS EXAMINED AND ANY ELEMENTS, COMPONENTS OR PORTIONS OF THE POT THAT WERE DETERMINED TO BE NONCOMPLIANT WITH THE CBC HAVE BEEN IDENTIFIED AND THE CORRECTIVE WORK NECESSARY TO BRING THEM INTO COMPLIANCE HAS BEEN INCLUDED WITHIN THE SCOPE OF THIS PROJECT'S WORK THROUGH DETAILS, DRAWINGS AND SPECIFICATIONS INCORPORATED INTO THESE CONSTRUCTION DOCUMENTS. ANY NONCOMPLIANT ELEMENTS, COMPONENTS OR PORTIONS OF THE POT THAT WILL NOT BE CORRECTED BY THIS PROJECT BASED ON VALUATION THRESHOLD LIMITATIONS OR A FINDING OF UNREASONABLE HARDSHIP ARE INDICATED IN THESE CONSTRUCTION DOCUMENTS.
DURING CONSTRUCTION, IF POT ITEMS WITHIN THE SCOPE OF THE PROJECT REPRESENTED AS CBC COMPLIANT ARE FOUND TO BE NONCONFORMING BEYOND REASONABLE CONSTRUCTION TOLERANCES, THE ITEMS SHALL BE BROUGHT INTO COMPLIANCE WITH THE CBC AS A PART OF THIS PROJECT BY MEANS OF A CONSTRUCTION CHANGE DOCUMENT.


EXISTING BUILDING INFORMATION

(E) MULTI-PURPOSE BUILDING 1	(E) CLASSROOM BUILDING 5
AREA: 11,520 SF	AREA: 7,851 SF
OCCUPANCY: E	OCCUPANCY: E
CONSTRUCTION TYPE: VB	CONSTRUCTION TYPE: VB
SPRINKLERED: NO	SFSPRINKLERED: NO

(E) ADMINISTRATION BUILDING 2	(E) CLASSROOM BUILDING 6
AREA: 2,877 SF	AREA: 8,723 SF
OCCUPANCY: B	OCCUPANCY: E
CONSTRUCTION TYPE: VB	CONSTRUCTION TYPE: VB
SPRINKLERED: NO	SPRINKLERED: NO

(E) LIBRARY BUILDING 3	(E) KINDERGARTEN BUILDING 7
AREA: 4,804 SF	AREA: 3,797 SF
OCCUPANCY: E	OCCUPANCY: E
CONSTRUCTION TYPE: VB	CONSTRUCTION TYPE: VB
SPRINKLERED: NO	SPRINKLERED: NO

(E) CLASSROOM BUILDING 4
AREA: 7,851 SF
OCCUPANCY: E
CONSTRUCTION TYPE: VB
SPRINKLERED: NO



BUILDING CODE DATA

(E) PORTABLE P4 & NEW PORTABLE P5:


OCCUPANCY:	E
CONSTRUCTION TYPE:	VB
BUILDING AREA:	2 X 960 = 1,920 SF
ALLOWABLE BUILDING AREA:	9,500 SF
NUMBER OF STORIES:	1
ALLOWABLE BUILDING HEIGHT:	1

LOAD FACTOR (CLASSROOM):	20 NET
# OF OCCUPANTS:	960/20 = 48

REQUIRED FIRE SEPARATION DISTANCE FOR TYPE VB, E OCCUPANCY = 10' FIRE SEPARATION DISTANCE PROVIDED = 10' BETWEEN P4 & BUILDING 6, 30' @ OTHER THREE SIDES; SEE OVERALL SITE PLAN

NOTES:
THE DESIGN PROFESSIONAL IN CHARGE HAS VERIFIED THAT NO FUEL-BURNING APPLIANCES OR FUEL-BURNING FIREPLACE WILL BE USED IN THE CLASSROOM. THE CLASSROOM WILL NOT BE SUPPLIED BY A FORCED-AIR FURNACE.

OVERALL SITE PLAN
1" = 60'-0"



810
FIRE & LIFE SAFETY SITE CONDITIONS SUBMITTAL

Division of the State Architect (DSA) documents referenced within this publication are available on the DSA Forms or DSA Publications webpages.
To facilitate the Division of the State Architect's (DSA) fire and life safety plan review of project site conditions, DSA requires the design professional to provide the following information at time of project submittal for projects consisting of construction of a new campus, construction of new building(s), additions to existing buildings, and for site alternate design means for fire department emergency vehicle access, and fire suppression water supply. Information associated with compliance items 1 through 3 below is to be provided for all project types indicated above. Information associated with items 4 through 7 is to be completed when an alternate means is utilized. Acknowledgement by the school district and signature from the Local Fire Authority (LFA) is only required when an alternate design means is being requested.
The Project Information and Fire & Life Safety Information sections are to be completed for all projects and imaged onto the fire access site plan. When an alternate design/means is proposed, all sections on pages 1 and 2 are to be completed and imaged on the fire access site plan.


PROJECT INFORMATION
School District/Owner: ORINDA UNION SCHOOL DISTRICT
Project Name/School: WAGNER RANCH ELEMENTARY PORTABLE PROJECT
Project Address: 350 CAMINO PABLO, ORINDA, CA 94603

FIRE & LIFE SAFETY INFORMATION

1. Has a fire hydrant flow test been performed within the past 12 months? (If yes, provide a copy of the test data.)	Yes <input type="checkbox"/>	No <input type="checkbox"/>
2. Was the fire hydrant water flow test performed as part of this LFA review?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
3. Is the project located within a designated fire hazard severity zone (FHSZ) as established by Cal-Fire? (If yes, indicate FHSZ classification below.)	Yes <input type="checkbox"/>	No <input type="checkbox"/>

Refer to the following website for FHSZ locations: <https://ca.fire.ca.gov/FSZ/>
Moderate High Very High

Wildland Interface Area (WIFA) (If any designations are checked, project design must meet the requirements of CBC Chapter 7A.)
WIFA



GENERAL NOTES


- A. SEE CIVIL AND ELECTRICAL DRAWINGS FOR RESPECTIVE SCOPE OF REMOVAL WORK.
- B. GENERAL CONTRACTOR RESPONSIBLE FOR LOCATING ALL UNDERGROUND UTILITY LINES AND COORDINATION WITH CONSTRUCTION PRIOR TO WORK.
- C. PROVIDE ANY AND ALL REMOVAL WORK NECESSARY TO ALLOW FOR INSTALLATION AND/OR CONSTRUCTION OF WORK TO BE PROVIDED.
- D. RESTORE, PATCH, REPAIR, REPLACE TO CONDITION PRIOR TO START OF CONSTRUCTION ANY EXISTING ITEM REMOVED OR OTHERWISE MODIFIED TO ALLOW FOR INSTALLATION OR CONSTRUCTION OF WORK TO BE PROVIDED.
- E. ALL FINISHES, INCLUDING BUT NOT LIMITED TO GROUND SURFACE, DISTURBED AS A RESULT OF CONSTRUCTION OR REMOVAL WORK SHALL BE RESTORED, PATCHED, REPAIRED, REPLACED, OR RECONSTRUCTED TO CONDITION PRIOR TO START OF CONSTRUCTION. FINISHED GROUND SURFACE TO MATCH EXISTING INCLUDING BUT NOT LIMITED TO GRADES/ELEVATIONS PRIOR TO START OF CONSTRUCTION. PREP AND PAINT ALL WORK PROVIDED THAT IS NOT FACTORY FINISHED. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE OF COLORS.
- F. PROVIDE ASSISTIVE LISTENING DEVICE SIGNAGE IN PORTABLE CLASSROOM AND ASSISTIVE LISTENING DEVICES AT MAIN OFFICE.

SHEET NOTES


- 32.05 ACCESSIBLE PARKING, S.C.D.
- 32.10 ACCESSIBLE VAN PARKING, S.C.D.

SITE PLAN LEGEND

- AREA OF SCOPE OF WORK
- NO WORK THIS BUILDING
- 20'-0" WIDE EMERGENCY VEHICLE ACCESS ROUTE
- INDICATES ACCESSIBLE PATH OF TRAVEL IS A BARRIER FREE ACCESS ROUTE WITHOUT ANY ABRUPT LEVEL CHANGES EXCEEDING 1/2" BEVELED AT 1:2 MAX. SLOPE OR VERTICAL LEVEL CHANGES NOT EXCEEDING 1/4" MAX. AND AT LEAST 48" WIDE. SURFACE IS SLIP RESISTANT, STABLE, FIRM AND SMOOTH. CROSS SLOPE DOES NOT EXCEED 2% AND SLOPE IN THE DIRECTION OF TRAVEL IS LESS THAN 5% UNLESS OTHERWISE INDICATED. ARCHITECT TO VERIFY THAT ALL BARRIERS IN THE PATH OF TRAVEL HAVE BEEN REMOVED UNDER THIS PROJECT AND PATH OF TRAVEL COMPLIES WITH CBC 11B.
- PROPERTY LINE
- ASSUMED PROPERTY LINE
- (E) FIRE HYDRANT
- B** ACCESSIBLE BOY'S RESTROOM TO SERVE AREA OF WORK, SEE 3/A2.01
- G** ACCESSIBLE GIRL'S RESTROOM TO SERVE AREA OF WORK, SEE 2/A2.01
- S** ACCESSIBLE STAFF RESTROOM TO SERVE AREA OF WORK, SEE 1/A2.01
- DF** ACCESSIBLE DRINKING FOUNTAIN TO SERVE AREA OF WORK, SEE 2/A2.03



HKIT ARCHITECTS
538 NINTH STREET SUITE 240 • OAKLAND, CA 94607
T 510 625 9800 • F 510 625 9801 • WWW.HKIT.COM



WAGNER RANCH ELEMENTARY SCHOOL RELOCATABLE PROJECT

350 CAMINO PABLO, ORINDA, CA 94563
JOB NO. 21010.03
DRAWN -
CHECKED -
JOB CAPTAIN -





DATE	DESCRIPTION
05.04.23	DSA SUBMITTAL
05.08.23	DSA BACKCHECK

ISSUE	DATE	DESCRIPTION


DRAWING TITLE
ENLARGED SITE PLAN

SCALE As indicated


A1.01



FOR DSA APPROVAL
THIS DRAWING REPRESENTS EXISTING
CONDITIONS FOR DSA APPROVAL.
NO WORK UNLESS NOTED AS NEW.




1 516 STAFF ALL GENDER RESTROOM - (E) PLAN
1/4" = 1'-0" DSA APP. # 01-102445




516 STAFF ALL GENDER RESTROOM - (E) INTERIOR ELEVATIONS
1/4" = 1'-0" NOTE: PATCH AND PAINT (E) GYP. BD. WALLS AS NECESSARY
FOLLOWING POSSIBLE RELOCATION OF ACCESSORIES; V.I.F.
USE ADULT AGE GROUP FOR FIXTURE AND ACCESSORY DIMENSIONS, SEE SHEET A2.03

FOR DSA APPROVAL
THIS DRAWING REPRESENTS EXISTING
CONDITIONS FOR DSA APPROVAL.
NO WORK UNLESS NOTED AS NEW.




2 609 GIRLS - EXISTING PLAN
1/4" = 1'-0" DSA APP# 64618




609 GIRLS - EXISTING INTERIOR ELEVATIONS
1/4" = 1'-0" USE AGE GROUP 9-12 FOR FIXTURE AND ACCESSORY DIMENSIONS, SEE SHEET A2.03

FOR DSA APPROVAL
THIS DRAWING REPRESENTS EXISTING
CONDITIONS FOR DSA APPROVAL.
NO WORK UNLESS NOTED AS NEW.



3 608 BOYS - EXISTING PLAN
1/4" = 1'-0" DSA APP# 64618



608 BOYS - INTERIOR ELEVATIONS
1/4" = 1'-0" USE AGE GROUP 9-12 FOR FIXTURE AND ACCESSORY DIMENSIONS, SEE SHEET A2.03

GENERAL NOTES

- A. ALL WORK TO BE COMPLETED TO INDUSTRY STANDARDS TO ENTIRETY.
- B. SEE STRUCTURAL, MECHANICAL AND ELECTRICAL DRAWINGS FOR RESPECTIVE SCOPE OF WORK.
- C. PROTECT ALL EXISTING FINISHES, FIXTURES AND EQUIPMENT THAT ARE TO BE EXPOSED DURING CONSTRUCTION WORK.
- D. ALL FINISHES TO BE EXPOSED THAT ARE DISTURBED AS A RESULT OF CONSTRUCTION WORK SHALL BE RESTORED, PATCHED, RECONSTRUCTED AND/OR PAINTED TO MATCH (E) BUILDING.
- E. FOR EXISTING PLUMBING FIXTURES AND/OR TOILET ACCESSORIES NOTED TO REMAIN, SEE DETAIL 29/A9 10 AND VERIFY ACCESS REQUIREMENTS.
- F. WHERE FIXTURES ARE RELOCATED AT EXISTING TILE FINISHES, REPLACE DAMAGED TILES TO MATCH ADJACENT FINISH.
- G. SEE SIGNAGE SCHEDULE FOR RESTROOM SIGNAGE.

DIMENSIONS ON ENLARGE TOILET ROOM PLANS AND ELEVATIONS ARE FROM F.O.F. (FACE OF FINISH) TYPICAL, U.O.N.

REMOVAL SHEET NOTES

- 2.30 (E) PLUMBING FIXTURE TO REMAIN, SEE DETAIL 20/A2.03 FOR ACCESS REQUIREMENTS
- 2.35 (E) TILE WAINSCOT TO REMAIN, PATCH / REPLACE DAMAGED / REMOVED TILES TO MATCH (E)




CONSTRUCTION SHEET NOTES

- 9.33 PATCH AS NECESSARY AND PAINT (E) INTERIOR WALL, CEILING AND TRIM TO LIKE NEW CONDITIONS; SEE INTERIOR FINISH SCHEDULE
- 10.10 PROVIDE TOILET PARTITION, SEE DETAIL 17 AND 22/A2.03 FOR ANCHORAGE DETAILS; SEE 25/A2.03 FOR TOE CLEARANCES
- 10.26 (E) LAVATORIES AND COUNTERTOP, SEE INTERIOR ELEVATIONS, SEE DETAIL 25/A2.03 FOR ACCESS REQUIREMENTS
- 10.28 (E) 42" GRAB BAR
- 10.29 (E) 36" GRAB BAR
- 10.30 (E) MIRROR
- 10.32 (E) SOAP DISPENSER, ADJUST HEIGHT ABOVE FINISH FLOOR PER 18&25/A2.03
- 10.38 (E) TOILET PAPER DISPENSER, ADJUST HEIGHT AND POSITION PER 20&25/A2.03
- 10.39 RE-INSTALL SALVAGED (E) 36" GRAB BAR TO OPEN SIDE OF FLUSH VALVE PER CBC 11B-604.5.2 EXCEPTION 2, LOWER GRAB BAR TO 9-12 AGE GROUP HEIGHT PER 25/A2.03; PROVIDE WALL BLOCKING PER 12/A2.03
- 10.40 SALVAGE AND LOWER (E) 42" GRAB BAR TO 9-12 AGE GROUP HEIGHT PER 25/A2.03; PROVIDE WALL BLOCKING PER 12/A2.03
- 10.41 (E) SEAT COVER DISPENSER; ADJUST HEIGHT OF OPENING TO 40" A.F.F.; SEE 18&25/A2.03
- 10.42 PROVIDE SANITARY NAPKIN RECEPACLE; SEE 20&25/A2.03
- 10.44 (E) PAPER TOWEL DISPENSER; ADJUST HEIGHT PER 25/A2.03
- 10.45 PROVIDE SEAT COVER DISPENSER; SEE 18&25/A2.03
- 10.46 PROVIDE 4" MAX. PROJECTION SURFACE MOUNTED PAPER TOWEL DISPENSER; SEE 18&25/A2.03
- 22.24 (E) LAVATORIES AND COUNTER TOP TO REMAIN
- 22.51 (E) FLOOR MOUNTED WATER CLOSET
- 22.54 (E) ACCESSIBLE WALL HUNG LAVATORY; SEE 19/A2.03 FOR (E) KNEE CLEARANCE

RESTROOM ACCESSORY SCHEDULE

MARK	DESCRIPTION	MANUFACTURER	MODEL	COMMENTS
A	36" GRAB BAR	BOBRICK	B-6806-36	
B	42" GRAB BAR	BOBRICK	B-6806-42	
C	SURFACE MOUNTED SEAT COVER DISPENSER	BOBRICK	B-221	
D1	SURFACE MOUNTED MULTI-ROLL TOILET TISSUE DISPENSER	BOBRICK	B-2888	AT ACCESSIBLE COMPARTMENTS
D2	SURFACE MOUNTED TOILET TISSUE DISPENSER	BOBRICK	B-6999	
E	SANITARY NAPKIN DISPOSAL	BOBRICK	B-270	
F	Bobrick B-221 Classic Series Surface Mounted Seat Cover Dispenser	Bobrick Washroom Equipment, Inc.	B-221	
F1	24" x 36" MIRROR WITH SHELF	BOBRICK	B-166	
F2	24" W X 36" H MIRROR	BOBRICK	B-1556	
G	Bobrick B-2111 Classic Series Surface Mounted Soap Dispenser	<varies>	B-2111	
H	SURFACE MOUNTED PAPER TOWEL DISPENSER	BOBRICK	B-2860	

KEY PLAN



WAGNER RANCH ELEMENTARY SCHOOL RELOCATABLE PROJECT

350 CAMINO PABLO, ORINDA, CA 94563
JOB NO. 21010.03
DRAWN -
CHECKED -
JOB CAPTAIN -


ISSUE

DATE	DESCRIPTION
05.04.23	DSA SUBMITTAL
05.08.23	DSA BACKCHECK


DRAWING TITLE
ACCESSIBLE RESTROOMS - REFERENCE PLANS & INTERIOR ELEVATIONS

SCALE As indicated


A2.01
COPYRIGHT © 2016 HKIT ARCHITECTS




1 PASSENGER DROP-OFF AND LOADING ZONE ENLARGED PLAN
1/4" = 1'-0"




2 LOT 1 - ACCESSIBLE PARKING DEMOLITION PLAN
1/4" = 1'-0"




3 LOT 1 - ACCESSIBLE PARKING CONSTRUCTION PLAN
1/4" = 1'-0"




9 LOT 2 - ACCESSIBLE PARKING DEMOLITION PLAN
1/4" = 1'-0"




10 LOT 2 - ACCESSIBLE PARKING CONSTRUCTION PLAN
1/4" = 1'-0"




5 POST FOOTING
3" = 1'-0"



6 NEW RAMP SECTION
1/4" = 1'-0"



7 HANDRAIL AT RAMP
3/4" = 1'-0"



8 NEW RAMP ENLARGED PLAN
1/4" = 1'-0"

**WAGNER RANCH
ELEMENTARY
SCHOOL
SCHOOL
SCOOTABLE
PROJECT**

350 CAMINO PABLO, ORINDA, CA
94563
JOB NO. 21010.03
DRAWN -
CHECKED -
JOB CAPTAIN -

ISSUE

DATE	DESCRIPTION
05.04.23	DSA SUBMITTAL
05.08.23	DSA BACKCHECK


DRAWING TITLE
SITE DETAILS

SCALE As indicated


A2.02
COPYRIGHT © 2016 HKIT ARCHITECTS



DATE	DESCRIPTION
05.04.23	DSA SUBMITTAL
05.08.23	DSA BACKCHECK




2 (E) ACCESSIBLE DRINKING FOUNTAIN
 1" = 1'-0"




12 GRAB BAR ATTACHMENT
 3" = 1'-0"


17 TOILET PARTITION WALL ANCHORAGE
 1 1/2" = 1'-0"



22 TOILET PARTITION FLOOR ANCHORAGE
 1 1/2" = 1'-0"




18 TOILET ROOM ACCESSORIES
 1/2" = 1'-0"



13 RESTROOM DOOR SIGN (RDS - X)
 1" = 1'-0"



19 LAVATORY DIAGRAM
 1/2" = 1'-0"




14 RESTROOM SIGN MOUNTING
 1/4" = 1'-0"

SIGNAGE SCHEDULE					
SIGN NO.	ROOM NO.	LOCATION	TYPE	DETAIL NO.	(SIGNAGE TYPE) OR SIGN TEXT
516	516	DOOR MOUNTED	RESTROOM DOOR SIGN	28C/A2.03	(GEOMETRIC SYMBOL C)
516A	516	WALL MOUNTED	TACTILE ROOM SIGN	30A/A2.03	STAFF ALL GENDER RESTROOM
608	608	DOOR MOUNTED	RESTROOM DOOR SIGN	28A/A2.03	(GEOMETRIC SYMBOL A)
608A	608	WALL MOUNTED	TACTILE ROOM SIGN	30C/A2.03	BOYS RESTROOM
609	609	DOOR MOUNTED	RESTROOM DOOR SIGN	28B/A2.03	(GEOMETRIC SYMBOL B)
609A	609	WALL MOUNTED	TACTILE ROOM SIGN	30D/A2.03	GIRLS RESTROOM
P5A	P5	WALL MOUNTED	TACTILE ROOM SIGN	21/A2.03	
P5B	P5	WALL MOUNTED	ASSISTIVE LISTENING DEVICE	27/A2.03	


RESTROOM FIXTURES/ACCESSORIES ALTERNATE DIMENSIONS			
2022 CBC Reference: T, Table, S, Section, F, Figure			
	ADULT	AGES 9-12	2022 CBC REFERENCE
A	FURTHEST T.P. DISPENSER IN FRONT OF W.C.	7" - 9" TO CENTERLINE	S 11B-604.7
B	TOILET OFFSET	17" - 18"	T 11B-604.9 S 11B-604.2
C	ACCESSORY HEIGHT	40" MAX.	40" MAX.
D	TOILET SEAT HEIGHT	17" - 19"	T 11B-604.9 S 11B-604.4
E	LAVSINK RIM HEIGHT	34" MAX.	T 11B-606.2 S 11B-606.3
F	URINAL HEIGHT	17" MAX.	S 11B-605.2
G	TOP OF GRAB BAR GRIPPING SURFACE	33" - 36"	T 11B-604.9 S 11B-604.4
H	LAVSINK KNEE CLEARANCE	27" MIN. (29" MIN. AT APRON OF LAVATORY)	S 11B-606.2 F 11B-306.3
J	T.P. DISPENSER OUTLET (A.F.F. TO CENTERLINE OF OUTLET OR ROLL)	19" MIN.	T 11B-604.9 S 11B-604.7
	URINAL PROJECTION	13 1/2" MIN.	S 11B-605.2
	URINAL FLUSH CONTROL HEIGHT	44" MAX.	S 11B-605.4
	HIGH D.F. SPOUT HEIGHT	38" - 43"	S 11B-602.7
	LOW D.F. APPROACH, SPOUT HEIGHT AND SPOUT LOCATION FROM FRONT EDGE OF THE UNIT INCLUDING BUMPERS	FRONT APPROACH PER 11B-306, 36" MAX. A.F.F. & 5" MAX. FROM FRONT EDGE OF THE UNIT	PARALLEL APPROACH IS PERMITTED IF SPOUT IS 30" MAX. A.F.F. & 3 1/2" MAX FROM FRONT EDGE OF THE UNIT
	D.F. OPERABLE PARTS	6" MAX. FROM FRONT EDGE OF THE UNIT	S 11B-602.3
	CANTILEVER D.F. PROJECTION	18" - 19"	S 11B-602.8
	TOE CLEARANCE AT TOILET PARTITION	9" MIN.	S 11B-604.8.1.4
	SHELF HEIGHT	40" - 48"	S 11B-604.8.3
	MIRROR HEIGHT (BOTTOM EDGE OF REFLECTING SURFACE)	40" MAX. (ABOVE LAVATORY OR COUNTERTOP) 35" MAX (NOT ABOVE LAVATORY OR COUNTERTOP)	S 11B-603.3
	MIRROR HEIGHT (BOTTOM EDGE OF REFLECTING SURFACE) IN DRESSING, FITTING & LOCKERROOMS	20" MAX	S 11B-803.6
	COAT HOOK HEIGHT	46"	T 11B-308.4

NOTE: ALL HEIGHT DIMENSIONS ARE A.F.F. (OR A.F.G. FOR EXTERIOR). ALL HORIZONTAL DIMENSIONS ARE TO FACE-OF-FINISH
 * AT SLOPING FLOORS, DIM. IS AT FACE OF FIXTURE


25 TOILET ROOM DIMENSIONS
 1/2" = 1'-0"




3 (E) VAN ACCESSIBLE PARKING SIGN
 1" = 1'-0"




4 (E) ACCESSIBLE PARKING SIGN
 1" = 1'-0"



5 (E) TOW AWAY SIGN
 1" = 1'-0"



9 ROOM IDENTIFICATION SIGN
 1 1/2" = 1'-0"



10 ASSISTIVE LISTENING SIGN
 1 1/2" = 1'-0"

15 RESTROOM WALL SIGN (RWS - X)
 1" = 1'-0"

20 WATER CLOSET/GRAB BAR DIAGRAM
 1/2" = 1'-0"

25 TOILET ROOM DIMENSIONS
 1/2" = 1'-0"


**WAGNER RANCH
 ELEMENTARY
 SCHOOL -
 PORTABLE**

350 Camino Pablo
 Orinda, Ca. 94563
 JOB NO. 21010.03
 DRAWN S.M.
 CHECKED M.V.
 JOB CAPTAIN M.V.
 ISSUE

05/04/23
DSA SUBMITTAL

DRAWING TITLE
**ELECTRICAL
 SITE PLAN**

SCALE: AS NOTED
E1.01
 COPYRIGHT © 2023 HKIT ARCHITECTS




- SHEET NOTES:**
- 1 EXISTING IN-GROUND PULLBOX. ROUTE NEW FEEDER THRU PULLBOXES (NEW TRENCH).
 - 2 PS FEEDER.
 - 3 (E) (1) 2" COMM, (1) 1 1/2" CLOCK/PAGING, (1) 1 1/2" FIRE ALARM.
 - 4 (E) FACP, RECORD DOCUMENT CABINET, AND COMMUNICATOR IN ADMINISTRATION. SEE 2/E1.01
 - 5 (N) VEP PANEL IN ADMINISTRATION. SEE 9/E0.01 & 2/E1.01
 - 6 "ADM" & "AIM" FOR VEP TRIGGER & TROUBLE.
 - 7 ADD S/S1 FIRE ALARM CABLE AND DATA CABLES FOR P5.
 - 8 ADD S1 CABLE.

USA
 PRIOR TO DIGGING CALL:
 UNDERGROUND SERVICE ALERT
 U.S.A.
 1-800-642-2444



(E) FIRE ALARM PANEL



VEP PANEL LOCATION

2 FACP / VEP LOCATION
 E1.01 SCALE: NONE

1 ELECTRICAL SITE PLAN
 E1.01 SCALE: 1" = 20'-0"

PLAN NORTH TRUE NORTH

0 10 20 40 FEET

**WAGNER RANCH
 ELEMENTARY
 SCHOOL -
 PORTABLE**


350 Camino Pablo
 Orinda, Ca. 94563
 JOB NO. 21010.03
 DRAWN S.M.
 CHECKED M.V.
 JOB CAPTAIN M.V.

ISSUE

05/04/23	DSA SUBMITTAL

DRAWING TITLE
**ELECTRICAL
 POWER, LOW VOLTAGE
 AND FIRE ALARM PLAN**

SCALE: AS NOTED
E2.01




SHEET NOTES


- 1 PANEL SUPPLIED WITH BUILDING.
- 2 CONNECT TO LIGHTING CIRCUIT AHEAD OF CONTROL.
- 3 18"x18"x6" DEEP NEMA 3R PULLBOX FOR LOW VOLTAGE CABLES AND FIRE ALARM. LOCATE AT TOP OF WALL.
- 4 (E) FA PULLBOX.
- 5 (E) COMM PULLBOX.
- 6 (E) ELEC PULLBOX.
- 7 (1) 2"C. AND (1) 1 1/2"C. FOR COMM CABLES FROM COMM BOX TO BUILDING.
- 8 IF CAMPUS NOT UPGRADED TO IP CLOCK SPEAKER PROVIDE 3#10 FOR CLOCK. PICK UP CLOCK CIRCUIT AT COMM BOX AND 2#22 OSP FOR SPEAKER TO TERMINALS AT BUILDING 6. COORDINATE CONNECTION AT (E) CONSOLE.

2 ELECTRICAL FIRE ALARM PLAN
 SCALE: 1/8" = 1'-0"
 PLAN NORTH

1 ELECTRICAL POWER AND LOW VOLTAGE PLAN
 SCALE: 1/8" = 1'-0"
 PLAN NORTH




3 CLOCK / SPEAKER DIAGRAM
 SCALE: NONE



HKIT ARCHITECTS
538 NINTH STREET SUITE 240 • OAKLAND, CA 94607
T 510 625 9800 • F 510 625 9801 • WWW.HKIT.COM



BWF
CONSULTING ENGINEERS
ELECTRICAL ENGINEERS
220 SO. SPRUCE AVENUE, SUITE 203
SO. SAN FRANCISCO, CALIFORNIA 94080
(650) 871-0200



DATE SIGNED: Apr. 26, 23

WAGNER RANCH ELEMENTARY SCHOOL - PORTABLE

350 Camino Pablo
Orinda, Ca. 94563

JOB NO. 21010.03

DRAWN S.M.

CHECKED M.V.

JOB CAPTAIN M.V.

ISSUE


DATE	DESCRIPTION
05/04/23	DSA SUBMITTAL

DRAWING TITLE
**ELECTRICAL
SINGLE LINE DIAGRAM
AND LOAD SUMMARY**

SCALE: AS NOTED

E3.01

COPYRIGHT © 2023 HKIT ARCHITECTS



1 SINGLE LINE DIAGRAM
E3.01 SCALE: NTS

**WAGNER RANCH
 ELEMENTARY
 SCHOOL -
 PORTABLE**

350 Camino Pablo
 Orinda, Ca. 94563

JOB NO. 21010.03
 DRAWN S.M.
 CHECKED M.V.
 JOB CAPTAIN M.V.

ISSUE

05/04/23	DSA SUBMITTAL

DRAWING TITLE
**ELECTRICAL
 FIRE ALARM RISER
 DIAGRAM AND
 CALCULATIONS**

SCALE: AS NOTED

E5.01

VOLTAGE DROP CALCULATION FOR : WAGNER RANCH ES
 DESCRIPTION: INDICATING CIRCUIT # PS NO P4 CIRCUIT 1

Node Ref	Unit AMP	Total AMP	Conductor Length (ft.)	AWG Size	Circular Mils	OHM Resistance per Foot	Voltage Drop *
1	0.148	0.148	170	12	6530	0.0020	0.1096
2	0.136	0.283	110	12	6530	0.0020	0.1245

TOTAL VOLTAGE DROP 0.2252
 PERCENT VOLTAGE DROP 1.10%

BASED ON A 20.4 VOLT CIRCUIT OPERATING AT 50 DEGREES

* (CIRCUIT LENGTH x 2)(LOAD IN AMPS)(RESISTANCE PER FOOT)

VOLTAGE DROP CALCULATION FOR : WAGNER RANCH ES
 70 VOLT CIRCUIT SPEAKER CIRCUITS


Speaker Circuit	Total watts	Total AMP	Circuit Length (ft.)	AWG Size	OHM Resistance	Voltage Drop *	% Voltage Drop
1	2.0	0.029	800	12	0.0020	0.0914	0.1537
Total	2.0						

*BASED ON 59.5 VOLTS OPERATING AT 75 DEGREES AND FULL LOAD FOR FULL LENGTH

ALL EXISTING ADDRESSES NOT AVAILABLE VERIFY AT PROJECT START

SLC 1-ADDRESS	TYPE	CODE LABEL	DEVICE LOCATION
D 43	Heat	Heat	Classroom P3
D 44	Photo	Smoke	Classroom P3
D 45	Photo	Smoke	Classroom P3
D 46	Heat	Heat	Classroom P3
D 47	Photo	Smoke	Classroom P4
D 48	Heat	Heat	Classroom P4
D 49	Photo	Smoke	Classroom P4
D 50	Heat	Heat	Classroom P4
M 98	Monitor	VEP Trigger	Administration
M 99	Monitor	VEP Trouble	Administration

2 PARTIAL ADDRESS LIST - DETECTORS
 SCALE: NTS



1 FIRE ALARM RISER DIAGRAM
 SCALE: NTS

JOB# 4815

MODULAR CLASSROOM BUILDING

MOBILE MODULAR

BUILDING SIZE: 24'x40'

STOCKPILE

BUILDING DATA

STRUCTURAL DESIGN: ORDINARY MOMENT RESISTANT FRAME
 TYPE OF CONSTRUCTION: V-N
 WIND LOAD (EXP C): 80 MPH
 SEISMIC ZONE 4, SEISMIC SOURCE TYPE A, DISTANCE 41.28 MILES
 $Z = .4$ $I = 1.0$ $C_v = 1.28$ $N_v = 2.0$
 $R = 4.0$ $C_u = 0.66$ $N_u = 1.5$ $SOL TYPE = 5p$
 FLOOR LIVE LOAD: 80 PSF
 ROOF LIVE LOAD: 20 PSF
 OCCUPANCY: 24'x40' CLASSROOM: E-2
 BUILDING AREA: 24'x40' BUILDING - 960 SF
 COMPLIES WITH CHAPTER 7-105 (1) - 1P
 THIS PD IS DESIGNED STRUCTURALLY TO SUPPORT THE WEIGHT OF A FIRE SPRINKLER SYSTEM.

APPLICABLE CODES

2001 CALIFORNIA BUILDING CODE (CBC), VOLUMES 1, 2, AND 3 (PART 2, TITLE 24, CCR) (1997 EDITION UNIFORM BUILDING CODE WITH 2001 CALIFORNIA AMENDMENTS)
 2001 CALIFORNIA ELECTRICAL CODE (CEC), (PART 3, TITLE 24, CCR)
 (1999 EDITION NATIONAL ELECTRICAL CODE WITH 2001 CALIFORNIA AMENDMENTS)
 2001 CALIFORNIA MECHANICAL CODE (CMC), (PART 4, TITLE 24, CCR)
 (2000 EDITION UNIFORM MECHANICAL CODE WITH 2001 CALIFORNIA AMENDMENTS)
 2001 CALIFORNIA PLUMBING CODE (CPC), (PART 6, TITLE 24, CCR)
 (2000 EDITION UNIFORM PLUMBING CODE WITH 2001 CALIFORNIA AMENDMENTS)
 2001 CALIFORNIA FIRE CODE (PART 8, TITLE 24, CCR)
 2001 CALIFORNIA BUILDING STANDARDS ADMINISTRATIVE CODE (PART 1, TITLE 24, CCR)
 2001 CALIFORNIA ENERGY CODE (PART 5, TITLE 24, CCR)
 2001 CALIFORNIA REFERENCED STANDARDS CODE (PART 12, TITLE 24, CCR)
 TITLE 19, CCR PUBLIC SAFETY, STATE FIRE MARSHAL REGULATIONS.

LEGEND

SYMBOL	DESCRIPTION
	DETAIL (1) ON SAME SHEET AS SYMBOL
	DETAIL (1) ON SHEET (2)
	KEY NOTE (1) ON SAME SHEET AS SYMBOL
	SECTION "A" ON SHEET (2)
	REVISION/CHANGE IN DRAWING. (1) IS FIRST REVISION
	HIGHLIGHTS CHANGED AREA
	DOOR REFERENCE
	WINDOW REFERENCE
	ELECTRICAL ITEM(S) SEE ELECTRICAL DRAWINGS
	HEATING/VENTILATING & AIR CONDITIONING ITEM(S) SEE MECHANICAL DRAWINGS
	PLUMBING ITEM(S) SEE MECHANICAL DRAWINGS
	STRUCTURAL ITEM(S) SEE STRUCTURAL DRAWINGS
	FINISH ITEM(S) SEE FINISH SCHEDULE
	RAMP - SEE RAMP DRAWINGS

ABBREVIATIONS

AGC - ABOVE GRADE CONCRETE
 BGC - BELOW GRADE CONCRETE
 DIA - DIAMETER
 CLR - CLEAR
 GA - GALVANNE
 MAX - MAXIMUM
 MIN - MINIMUM
 N/C - NOT IN CONTRACT
 NTS - NOT TO SCALE
 OC - ON CENTER
 OD - OUTSIDE DIAMETER
 OSB - ORIENTED STRAND BOARD
 ROH - ROOF OVERHANG
 SH - SHIM
 STS - SELF TAPPING SCREW
 STSMS - SELF TAPPING SHEET METAL SCREW
 TYP - TYPICAL
 UN - UNLESS OTHERWISE NOTED

WITH THE SHOWING OF THESE DRAWINGS, WE ACKNOWLEDGE THAT WE HAVE REVIEWED THESE PLANS AND SPECIFICATIONS AND HAVE FOUND THEM TO BE IN GENERAL COMPLIANCE WITH THE BID DRAWINGS, SPECIFICATIONS AND ASSOCIATED ADDENDA. WHEN THESE PLANS AND SPECIFICATIONS HAVE BEEN APPROVED BY THE DIVISION OF THE STATE ARCHITECT, THEY SHALL PREVAIL OVER CONFLICTING AREAS IN THE BID DRAWINGS AND SPECIFICATIONS, AND ANY ADDENDA THEREOF.

CONFIDENTIAL - THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF MODTECH, INC. UNAUTHORIZED COPYING, DISCLOSURE OR OTHER UNAUTHORIZED USES ARE PROHIBITED.

PROJECT NUMBER: 4815
 MOBILE MODULAR

MODTECH, INC. 2002
 ALL RIGHTS RESERVED

DATE: 07/07/03
 DRAWN BY: [Signature]
 CHECKED BY: [Signature]
 DATE: [Signature]

COVER SHEET

SHEET INDEX

ARCHITECTURAL

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
 MODTECH, INC.

REVIEWED FOR
 SS FLS ACS

DATE: 5/17/2023

STRUCTURAL

S1.0 - FOUNDATION PLAN - SEE E-1000
 S1.1 - FOUNDATION DETAILS - SEE E-1000
 S1.2 - FLOOR FINISH PLAN - 80 PSF LL
 S1.3 - FLOOR FINISH DETAILS (TYPICAL)
 S1.4 - ROOF FINISH PLAN (DUAL FINISH) BY FINISH
 S1.5 - ROOF FINISH DETAILS (TYPICAL)
 S1.6 - WALL FINISH PLAN - SEE FINISH SCHEDULE
 S1.7 - WALL FINISH DETAILS (TYPICAL)
 S1.8 - WALL FINISH DETAILS (TYPICAL)
 S1.9 - WALL FINISH DETAILS (TYPICAL)
 S1.10 - WALL FINISH DETAILS (TYPICAL)
 S1.11 - WALL FINISH DETAILS (TYPICAL)
 S1.12 - WALL FINISH DETAILS (TYPICAL)
 S1.13 - WALL FINISH DETAILS (TYPICAL)
 S1.14 - WALL FINISH DETAILS (TYPICAL)
 S1.15 - WALL FINISH DETAILS (TYPICAL)
 S1.16 - WALL FINISH DETAILS (TYPICAL)
 S1.17 - WALL FINISH DETAILS (TYPICAL)
 S1.18 - WALL FINISH DETAILS (TYPICAL)
 S1.19 - WALL FINISH DETAILS (TYPICAL)
 S1.20 - WALL FINISH DETAILS (TYPICAL)

MECHANICAL

M1.0 - MECHANICAL (HVAC) PLAN - 4 TON
 M1.1 - MECHANICAL (HVAC) PLAN - 8 TON
 M1.2 - MECHANICAL (HVAC) PLAN - 12 TON

ELECTRICAL

E1.0 - ELECTRICAL PLAN
 E1.1 - ELECTRICAL PLAN
 E1.2 - ELECTRICAL PLAN

RAMP

R1.0 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.1 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.2 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.3 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.4 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.5 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.6 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.7 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.8 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.9 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.10 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.11 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.12 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.13 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.14 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.15 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.16 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.17 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.18 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.19 - RAMP PLAN - SEE FINISH SCHEDULE
 R1.20 - RAMP PLAN - SEE FINISH SCHEDULE

DBS State of California - Department of General Services - City Dev't, Governor
 DIVISION OF THE STATE ARCHITECT
 Headquarters: 1145 R Street, Suite 1911 - Sacramento, CA 95834 - (916) 445-8100

PC-04-104796

STRUCTURAL TESTS AND INSPECTIONS

Test/Inspection	Code	Remarks
Foundation tests		
Soil strength		
Concrete strength		
Reinforcement		
Formwork		
Structural steel		
Welding		
Composite steel		
Other		

~~IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 MODTECH, INC.
 DATE: 5/17/2023
 ACC: Karen Deane, Architect~~

~~IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 MODTECH, INC.
 DATE: 5/17/2023
 ACC: D. Shay
 ACC: CRUSH~~

PC
CBC 2001

NOTES

SECTION 05134.01 OF THE 2001 CBC
 ALL WELDS IN PRIMARY MEMBERS AND CONNECTIONS IN THE LATERAL FORCE-RESISTING SYSTEM SHALL BE MADE WITH A FILLER METAL THAT HAS A MINIMUM CHARPY V-NOTCH TOUGHNESS OF 20 FT-LBS AT MINUS 20 DEGREES F.

Professional Engineer Seal
 PC Professional of Record Seal
 Architect Seal

MODTECH, INC.
 2830 BARRETT AVENUE FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427

COVER SHEET


A.0

PROJECT NO. 4815
 PC-04-104796
 105483

KEY NOTES



1 ROOF OVERHANG
 2 HVAC UNIT
 3 2 -
 4 FRESH AIR
 5 INTERIOR
 6 FIRE WALL
 7 MOULDED
 8 ELECTRICAL
 9 RAMP
 10 STORAGE OCCUPANCY

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023




NOTES

1. METAL TAG ON ALL MODULES. MECHANICALLY ATTACHED TO REAR EXTERIOR OF BUILDING SHOW D.S.A. APPLICATION NUMBER, MANUFACTURER'S NAME AND SERIAL NUMBER.
2. METAL TAG MIN. 3 1/2"x1 1/2" STAMPED METAL I.D. W/
 1. OPSC BUILDING NUMBER
 2. DESIGN WIND LOAD
 3. DESIGN ROOF LOAD
3. PROVIDE MIN. 3 1/2"x1 1/2" METAL TAG INSTALLED INSIDE THE ELECTRICAL PANEL SHOWING OPSC NUMBER AND DSA NUMBER.



FLOOR PLAN OPTION-1 SCALE: 1/4" = 1'-0"

REVISIONS	MECHANICAL ENGINEER'S SEAL	Mechanical Engineer's Seal	PC Professional of Record Seal	Architect Seal	PC CBC 2001	PROJECT NUMBER: 4815 MOBILE MODULAR	MODTECH, INC. 2002 ALL RIGHTS RESERVED	DRAWN BY: CL DATE: 07/07/03 CHECKED BY: DATE:									
<table border="1" style="width: 100%; height: 40px;"> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table>															2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427	© MODTECH, INC. 2002 ALL RIGHTS RESERVED	DRAWN BY: CL DATE: 07/07/03 CHECKED BY: DATE:
FLOOR PLAN						A1.1											

PROJECT NO. 4815

KEY NOTES

- 1 MAIN RUNNERS @ 4'-0" W/12GA. HANGER WIRES @ END OF EACH RUNNER.
- 2 AT THE END OF HANGER WIRE OF WALL
- 3 VERTICAL PLUMB
- 4 PROVIDE FIXTURE ATTACHED TO RECESS METAL
- 5 RUNNERS AT 2'-ADJ. ATTACHMENT, CLEARANCE OF 1/2" BETWEEN END OF RUNNERS AND FACE OF WALL
- 6 CEILING AREAS SHALL HAVE 2/4-WAY SPLAYS PER DETAIL 1 ON SHEET A2.09 IN LOCATIONS INDICATED ON DRAWINGS. WIRES TAUT BUT NOT TO DISTORT GRID.
- 7 T-BAR PART NUMBERS

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
REVIEWED FOR

SS FLS STACS

DATE: 5/17/2023

T-BAR PART NUMBERS

	AMERICAN FA-041		
RUNNER	7301D		
4' CROSS TEE	7343		
2' CROSS TEE	7328		
WALL ANGLE	7800D		

- 8 DUCTWORK SHALL BE RIGIDLY ATTACHED TO BUILDING AND SHALL NOT BE CLOSER THAN 6" TO HANGER WIRES.
- 9 REGISTERS SHALL BE POSITIVELY ATTACHED W/4-10GA. SHEET METAL SCREWS. (TYP. 1- @ EA. CORNER)
- 10 CEILING PANELS: 2010


IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

04 10 33


JUL 1 2003

LEGEND

- T & T BAR CEILING
- 2'X 4' ELEC. FIXTURE RECESSED
- SUPPLY AIR DIFFUSER
- RETURN AIR DIFFUSER
- SPLAY WIRE 4 WAY
- INDICATES FIXED SIDE (SEE DETAIL 7/A2.09)
- INDICATES FREE SIDE (SEE DETAIL 6/A2.09)



OPTION-1




OPTION-2

REFLECTED CEILING PLAN (24'X40')
SCALE: 1/4" = 1'-0"

<p>REVISIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 5%;">NO.</td> <td style="width: 70%;">DESCRIPTION & MODIFIED REFLECTED C.L.D.</td> <td style="width: 25%;">DATE</td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	NO.	DESCRIPTION & MODIFIED REFLECTED C.L.D.	DATE				<p>Architect's Seal</p>	<p>Mechanical Engineer's Seal</p>	<p>Professional of Record's Seal</p>	<p>Architect's Seal</p>	<p>PC CBC 2004 PC-04 104798</p>	<p>MODTECH™ 2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427</p>	<p>PROJECT NUMBER: 4815 MOBILE MODULAR</p>	<p>MODTECH, INC. 2002 ALL RIGHTS RESERVED</p>	<p>DRAWN BY: CL DATE: 07/07/03 CHECKED BY: DATE:</p>
NO.	DESCRIPTION & MODIFIED REFLECTED C.L.D.	DATE													
REFLECTED CEILING PLAN 12 LIGHTS							A2.04								


PROJECT NO. 4815
PC-04-104798



ALTERNATE

TYPICAL FIXED SIDE


7



NOTE: CONDUIT MAY BE CRIMPED ON EITHER SIDE OF T-BAR, DEPENDING UPON CONDITION & LOCATION


ALT. CONN. AT BOTTOM

4




SEISMIC SPLAY - 4 WAY

1




5



NOTE: LAY-IN CEILING TILE NOT SHOWN FOR CLARITY.

GRID AT MOD LINE


2



ALTERNATE

TYPICAL FREE SIDE

6




NOTE: CONDUIT MAY BE CRIMPED ON EITHER SIDE OF T-BAR DEPENDING UPON CONDITION & LOCATION

3


KEY NOTES

- 1 12GA HANGER OR DIAGONAL SPLAY WIRE IN PUNCHED OR DRILLED HOLE
- 2 12 GA R
- 3 M
- 4 1
- 5 W
- 6 6
- 7 AN
- 8 CONN
- 9 TOP PLATE
- 10 #10 S.T.S.M.S. @ 4' O.C.
- 11 3" X 1/4" EYED SCREW, 1/8" X 2" JIF-E SCREW WHEN METAL STUDS ARE USED
- 12 HANGER TO WALL WHERE NO RAFTER ABOVE, MAX SLOPE 1" IN 6"
- 13 28 GA. JETCOAT
- 14 CROSS TEE
- 15 12GA. HANGER WIRE AT THE END ON EACH RUNNER MIN. 4 WRAPS IN MAX 1 1/2" - SEE DETAIL #5 FOR WIRE TO PURLIN ATTACHMENT
- 16 MAIN RUNNERS OR CROSS TEES
- 17 ACOUSTICAL BOARD
- 18 FINISH WALL
- 19 HORIZONTAL STRUTS SHALL RUN CONTINUOUS AT ALL PERIMETERS, NOT POP RIVETED TO THE WALL ANGLE ARMSTRONG #7425 OR #7445 WITH SPRING STEEL SNAP TO RUNNER PER IR M-3
- 20 3/4" EMT CONDUIT - MAX 5'-2" (COMPRESSION STRUT)
- 21 CRIMP CONDUIT AND ATTACH TO RAFTER WITH (1) #8 TEK SCREW
- 22 PROVIDE SPACE AT ALL MEMBERS AT OPPOSITE WALL
- 23 CRIMP CONDUIT AND ATTACH TO T-BAR GRID WITH (1) #8 TEK SCREW
- 24 ROOF BEAM SEE (B)
- 25 ROOF PURLIN SEE (B)

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023



Notes:
 1. THIS DRAWING TO BE PROVIDED AT BUILDING LEVEL - AT ALL WALLS - THIS DRAWING MAY BE USED - WITHOUT BOARD, EXCEPT PAPER BAND OR STRIPS OR SLATS, OF MINERAL OR GLASS FIBER INSULATION PER CBC SECTION 708.2.2.



NO.	REVISION	DATE	BY	CHKD.


Professional Engineer's Seal
 Mechanical Engineer's Seal
 PE Professional of Record Seal
 Architect's Seal

PC
 CBC 2001
 MOORTECH™
 2830 BARRETT AVENUE FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427

PROJECT NUMBER: 4815
 MOBILE MODULAR
 © MOORTECH, INC. 2002
 ALL RIGHTS RESERVED
 REFLECTED CEILING DETAILS

DRAWN BY: CL
 DATE: 07/07/03
 CHECKED BY:
 DATE:
 A2.09

PROJECT NO. 4815



ROOF PLAN (DUAL SLOPE) (24'X40')
SCALE: 1/4" = 1'-0"


KEY NOTES

1 DOWNSPOUT (TYPICAL 1" X 3" X 30")
 2 CO
 3 22"
 4 ME
 5 RI

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023


NOTES

1. BUILDING HOUSING GROUP E OCCUPANCIES SHALL HAVE ROOF COVERINGS AS SPECIFIED IN TABLE 15A. C.B.C. CLASS A



<p>REVISIONS</p> <table border="1"> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </table>																	<p>Engineer's Seal</p>	<p>Mechanical Engineer's Seal</p>	<p>Professional of Record Seal</p>	<p>Architect's Seal</p>	<p>PC CBC 2001 10/7/99</p>	<p>MODTECH™ 2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427</p>	<p>PROJECT NUMBER: 4815 MOBILE MODULAR</p>	<p>© MODTECH, INC. 2002 ALL RIGHTS RESERVED</p>	<p>DRAWN BY: [Signature] DATE: 07/07/03 CHECKED BY: [Signature] DATE:</p>
<p>ROOF PLAN</p>						<p>A3.01</p>																			

FILE PATH: PROJECT NO. 4815



- KEY NOTES**
- 1 TYP. INTERIOR FINISH
 - 2 IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-120975 INC:
REVIEWED FOR
 - 3 SS FLS STACS
 - 4 DATE: 5/17/2023
 - 5 SEALANT TYP. (SEE SPECIFICATIONS)
 - 6 EXTERIOR WALL (SEE S5.0 FOR CONNECTIONS)
 - 7 #14 STMS AT EA STANDING RIB (16" OC)
 - 8 DOWNSPOUT
 - 9 #8 STMS - 1 AT EA SIDE OF DOWNSPOUT TO BRACKET
 - 10 NOT USED
 - 11 ATTACHMENT BRACKET (TOP 3 PLACES, TOP BOTTOM & MIDSPAN W/ 2 #10 STMS - BRACKET TO STUD) - SEE NOTE AT DETAIL B
 - 12 2 X 4 SILL PLATE PER 1/55-1
 - 13 ROOF HEADER SEE [STR]
 - 14 1/4" GAP w/ 3/8" DIA BACKER ROD
1/4" CAULKING/COLOR CAULK, MATCH PAINT
 - 15 STANDING SEAM ROOF (SEE A3.01 FOR GA.)
 - 16 ROOF PURLIN SEE [STR]
 - 17 FLOOR BEAM SEE [STR]
 - 18 22GA GALV FLASHING (AT BELOW GRADE CONG. FOUNDATION ONLY)
 - 19 CONTINUOUS 28GA. GUTTER (SEE DETAIL #9)
 - 20 INSULATION (SEE SPECS FOR TYPE AND SIZE)
 - 21 #14 STMS AT EACH CLIP (32" O.C.)
 - 22 22 GA STARTER/END ROOF CLIP-DETAIL #3
 - 23 1/4" CONTINUOUS BEAD OF SEALANT AROUND ENTIRE PERIMETER OF FRAME
 - 24 #10 STMS WITH NEOPRENE WASHER FOR FLASHING INTO ROOF BEAM @ 24" O.C.
 - 25 20 GA GALVANIZED IRON FLASHING AT SIDE WALL
 - 26 C 14x12 GA HEADER
 - 27 (2) 22 GA STANDING SEAM ROOF PAN
 - 28 22 GA STANDING SEAM ROOF PAN
 - 29 22 GA ROOF CLIP (AT EA PURLIN)
 - 30 PROVIDE VAPOR BARRIER OVER INSULATION AT ROOF BEAMS AND CEILING
 - 31 1/4" GAP w/ 3/8" BACKER ROD
 - 32 1/4" CAULKING/COLOR CAULK, MATCH PAINT

REVISIONS

Professional Engineer's Seal
 Mechanical Engineer's Seal
 PE Professional of Record Seal
 Architect's Seal
 PC
 CBC 2001
 10/17/08


MODTECH™
 2830 BARRETT AVENUE FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427

PROJECT NUMBER: 4815
 MOBILE MODULAR
ROOF DETAILS


MODTECH, INC. 2002
 ALL RIGHTS RESERVED
 OWNED BY: CL
 DATE: 07/07/03
 CHECKED BY: [Signature]
 DATE: [Signature]

A3.03


PROJECT N 4815




1 FRONT ELEVATION
OPTION-2 OPP-HAND
1/4" = 1'-0"



2 LEFT ELEVATION
1/4" = 1'-0"



3 REAR ELEVATION
OPTION-2 OPP-HAND
1/4" = 1'-0"





4 RIGHT ELEVATION
1/4" = 1'-0"

KEY NOTES

- 1 TYPICAL EXTERIOR SIDING (SEE A6.02)
- 2 EXTERIOR IDENTIFICATION STAMP
- 3 TO DIV. OF THE STATE ARCHITECT
- 4 RA APP: 01-120975 INC:
- 5 HV REVIEWED FOR
- 6 SS FLS ACS
- 7 DATE: 5/17/2023
- 8 CONT. (LOCATION OF DOWNSPOUT SHOWN ON ROOF PLAN) SEE A3.01
- 9 SPLASH BLOCK (BY OTHERS)
- 10 FINISH FLOOR LINE
- 11 BOTTOM FLANGE OF FLOOR BEAM
- 12 ROOF HEADER
- 13 VENT. SEE FOUNDATION PLAN
- 14 FINISH GRADE
- 15 ROOF BEAM SEE (RM)
- 16 COLUMN SEE (RM)
- 17 ELECTRICAL STUB-OUT SEE (EL)
- 18 GROUND STUB-OUT SEE (EL)
- 19 J BOX FOR EXT. FA HORN SEE (EL)
- 20 NEMA 0" X 0" GUTTER BOX SEE (EL)
- 21 RIDGE
- 22 NOT USED
- 23 IF HVAC UNIT IS LOCATED IN ANY PATH OF TRAVEL OR CIRCULATION AREA AND HEIGHT FROM GRADE TO BOTTOM OF UNIT EXCEEDS 27" THEN PROTECTION MUST BE PROVIDED BY DISTRICT PRIOR TO OCCUPANCY.
- 24 BRIDGE PROVIDED AND INSTALLED BY DISTRICT PRIOR TO OCCUPANCY. SEE SHEET A6.02

NOTES

- 1. SEE FOUNDATION PLAN FOR SIZE AND LOCATION OF UNDER FLOOR VENTS.




<p>REVISIONS</p> <table border="1"> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table>										<p>Structural Engineer's Seal</p>	<p>Mechanical Engineer's Seal</p>	<p>PC Professional of Record Seal</p>	<p>Architect Seal</p>	<p>PC CBC 2001 OPERATION STOP OFFICE OF PROFESSIONAL REGULATION NO. 104786 DATE: 7/17/23</p>	<p>MODTECH™ 2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427</p>	<p>PROJECT NUMBER: 4815 MOBILE MODULAR</p>	<p>© MODTECH, INC. 2002 ALL RIGHTS RESERVED</p>	<p>DRAWN BY: GL DATE: 07/07/03 CHECKED BY: DATE:</p>	<p>PROJECT NO. 4815</p>
<p>EXTERIOR ELEVATIONS W/ FASCIA</p>							<p>A4.01</p>												

KEY NOTES

1 TYP. INTERIOR FINISH (SEE FINISH SCHEDULE)
 2 TYPICAL FINISH
 3 1/2" MAX.
 4 2X4
 5 CORNER
 6 DOWN
 7 TUB
 8 OUT
 9 #10
 10 2X FLOOR
 11 VINYL
 12 MODULE JOINT
 13 104 AT 24" O.C. FACE NAIL ON 104 AT 12" O.C. TOE NAIL (SEE SHEET SS.2)
 14 FLOOR BEAM SIZE (SIZ)
 15 PRESSED STEEL FRAME (R.O. TYPE SEE A6.02)
 16 ALUMINUM THRESHOLD (SEE HARDWARE SCHEDULE)
 17 FRESH LANDING SEE FLOOR PLAN AND FOUNDATION FOR TYPE AND FINISH
 18 DOOR AND DOOR BOTTOM (SEE HARDWARE SCHEDULE)
 19 (2) 2X4 KING STUD (SEE SHEET SS.0)
 20 2X4 TRIMMER (SEE SHEET SS.0)
 21 2" MOLD 200A
 22 4" AIRCO TRIM
 23 (2) 2X4 SILL PLATE W/ 104 AT 16" O.C.
 24 INSULATION (SEE SPECS. FOR SIZE AND TYPE)
 25 FRESH FLOORING (SEE FINISH SCHEDULE SHEET A6.02)
 26 2X4 HANG STUDS (SEE SHEET SS.0) DETAILS FOR NUMBER OF STUDS REQUIRED AND HANGING SCHEDULE FOR HANGING
 27 WINDOW GLAZING (SEE WINDOW SCHEDULE SHEET A6.02)
 28 2X6 LET IN (SEE WALL FRAMING SHEET C/S6.0)
 29 ALUMINUM WINDOW FRAME WITH NAIL-ON FINISH. INSTALL W/ NAIL 3" BLDG. PAPER BETWEEN FINISH AND FRAMING. INSTALL WITH 04 AT MAX. 24" O.C.
 30 104 BOX STAGGERED AT MAX. 24" O.C.
 31 HEADER 12/SS.0
 32 20 GA DRIP FLASH
 33 6-3/8" X 2" GALVANIZED LAG BOLTS
 34 L 1-1/2" X 1-1/2" X 1/8" LONG (BY HANG MFR.) ATTACHED TO A/C W/ #10 SELF TAPPING SHEET METAL SCREWS AND ATTACH TO WALL W/ 3/8" X 2" GALVANIZED LAG BOLTS
 35 SIDE OF HVAC UNIT SEE (SIZ)
 36 (3) 2X4 W/ PLYWOOD SPACERS- BUILT- UP POST. 04 AT O.C. STAGGERED BRACKET TO FIRST 2X4 104 AT 12" O.C. SECOND 2X4 104 AT 12" O.C. STAGGERED THIRD 2X4 ALTERNATE USE 4X4 POST
 37 110A, X24" STEEL SUPPORT BRACKET
 38 EN - 04 BOX ELECTRO ONLY. AT 8" O.C.
 39 FH - 04 BOX ELECTRO ONLY. AT 12" O.C.
 40 20 GA GALV. FLASHING (AT BELOW CRACK CONC. FOUNDATION ONLY)
 41 #8 STIMBS - 1 AT EA SIDE OF DOWNSPOUT TO BRACKET
 42 ATTACHMENT BRACKET (TYP 3 PLACES TOP, BOTTOM & MIDSPAN W/ 2-#10 STIMBS, BRACKET TO STUD) SEE NOTE AT DETAIL B

DATE: 5/17/2023

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS STACS
 DATE: 5/17/2023



20 DOWNSPOUT ATTACHMENT 16 SILL PLATE 12 DOOR JAMB 8 CORNER COLUMN 4

SCALE: 4"=1' (20)
 SCALE: 1 1/2"=1'-0" (16)
 SCALE: 3"=1'-0" (12)
 SCALE: 3"=1'-0" (8)

NOTE: DOWN SPOUT ATTACHES TO COLUMN AT FRONT AND TO STUD AT REAR IN ORDER TO MTS RAMP RAILING AT FRONT

NOTES

1. EN 04 ELECTRO ONLY. AT 8" O.C.
 2. FH 04 ELECTRO ONLY. AT 12" O.C.
 3. SEE SHEET SS.0 FOR TYPICAL WALL FRAMING HANGING

INSULATION MATERIALS INSULATED WITHIN FLOOR-CEILING ASSEMBLIES, ROOF-CEILING ASSEMBLIES, WALLS, CRAWL SPACES, OR ATTICS SHALL HAVE A FLAME-SPREAD RATING NOT TO EXCEED 25 AND A SMOKE DENSITY NOT TO EXCEED 450. EXCEPTIONS:
 A: FOAM PLASTIC INSULATION SHALL COMPLY WITH SEC. 2602
 B: WHEN MATERIALS ARE INSULATED IN CONCEALED SPACES OF TYPES I, II, IV, AND V CONSTRUCTION, THE FLAME SPREAD AND SMOKE-DEVELOPED LIMITATIONS DO NOT APPLY TO FACINGS. IF THE FACING IS INSTALLED IN SUBSTANTIAL CONTACT WITH THE UNINSULATED SURFACE OF THE CEILING, FLOOR OR WALL FINISH. (SEC. 707.3 CBC)

REVISIONS	MECHANICAL ENGINEER'S SEAL	MECHANICAL ENGINEER'S SEAL	PC PROFESSIONAL OF RECORD SEAL	ARCHITECT'S SEAL

Professional Engineer's Seal
 Mechanical Engineer's Seal
 PC Professional of Record Seal
 Architect's Seal

PC
 CBC 2001
 04 10 2023
 10 2023

MODTECH™
 2030 BARRETT AVENUE, PERRIS, CALIF. 92572
 FAX (909) 943-4014
 FAX (909) 940-0427

PROJECT NUMBER: 4815
 MOBILE MODULAR

ARCHITECTURAL DETAILS

© MODTECH, INC. 2002
 ALL RIGHTS RESERVED

DATE: 07/07/03
 CHECKED BY:
 DATE:

A4.03

PROJECT NO. 4815

KEY NOTES


- 1 TYPICAL INTERIOR FINISH (F2)
- 2 CLOSURE AT WINDOW TOP
- 3 DUP.
- 4 J.
- 5 L.
- 6 B.
- 7 R.
- 8 E.
- 9 F.
- 10 T.
- 11 M.
- 12 6040 P...
- 13 FIRE EXTINGUISHER: 5 LBS DRY CHEMICAL, WITH 2A-10BC UL RATING ON WALL MOUNTED BRACKET, HANDLE AT 45° AFF.
- 14 ELECTRIC CLOSET (E)
- 15 SEAT CABINET (OPTIONAL)

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT


APP: 01-120975 INC:
REVIEWED FOR

SS FLS ACS


DATE: 5/17/2023




1 LEFT ELEVATION



2 REAR ELEVATION





3 RIGHT SIDE ELEVATION



4 FRONT ELEVATION

INTERIOR ELEVATIONS
OPTION-1

SCALE: 1/4" = 1'-0" (24'x40')



<p>REVISIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table>													<p>Structural Engineer's Seal</p>	<p>Mechanical Engineer's Seal</p>	<p>PC Professional of Record Seal</p>	<p>Architect's Seal</p>	<p>PC CBC 2001</p>	<p style="text-align: center;">MODTECH™</p> <p>2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427</p>	<p>PROJECT NUMBER: 4815. MOBILE MODULAR</p>	<p>© MODTECH, INC. 2002 ALL RIGHTS RESERVED</p>	<p>DRAWN BY: QL DATE: 07/07/03 CHECKED BY: DATE:</p>
INTERIOR ELEVATIONS							24'x40'	A5.02													

PROJECT NO. 4815

DOOR SCHEDULE WINDOW SCHEDULE ROOM FINISH SCHEDULE NOTES

DOORS				FRAMES				NOTE NO.
DOOR NUMBER	FRAMING OPENING SIZE	MATERIAL	TYPE	MATERIAL	HEAD DETAIL	JAMB DETAIL	SILL DETAIL	
1	3'-0" x 6'-8"	HM	A	HM	7/A4.03	8/A4.03	1/A4.03	5-1/8"

AMT.	TYPE	WIDTH	HEIGHT	FINISH	WIN. NO.	CLASS TYPE
2	1	8'-0"	4'-0"	ANODIZED	A	7/32" MIN. SOLAR GRAY AN. DUAL GLAZE

ROOM NUMBER	ROOM NAME	FINISHES							REMARKS
		FLOOR	BASE	WALLS			CEILING		
1	CLASSROOM	A	D	F	F	F	F	L	8'-0"

1. ALL FINISHES TO BE IDENTIFIED BY DIVISION AND NUMBER.
 2. FOR SPECIFICATIONS, SEE DRAWING NOTES.



IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
 REVIEWED FOR

SS FLS ACS

DATE: 5/17/2023

- HM - HOLLOW METAL
- AL - ALUMINUM
- SST - STAINLESS STEEL
- STL - STEEL
- WWF - WINDOW WALL FRAME
- SC - SOLID CORE WOOD
- HC - HOLLOW CORE WOOD
- SCL - SOLID CORE WOOD LEGACY





- DOOR NOTES**
- DOOR HANDLES FOR LOCKSETS TO BE CENTERED @ 36" AFF & DEADBOLTS @ 44" AFF.
 - HARDWARE TO BE OPENABLE FROM THE INSIDE WITHOUT ANY SPECIAL KNOWLEDGE OR EFFORT. LEVERS TO RETURN TO WITHIN 1/2" OF DOOR.
 - ALL DOORS SHALL BE 1-3/4" THICK UNO.
 - DOUBLE LETTERS IN SCHEDULE, INDICATES A PAIR OF DOORS.
 - SAFETY GLASS, CLEAR
 - WIRE GLASS
 - UNDERCUT DOOR
 - FINED LOUVER
 - FURRIE LINK LOUVER
 - VISION PANEL
 - CLOSURE SHALL BE SET FOR MAXIMUM OPENING PRESSURE OF 5 LBS ON ALL DOORS

- WINDOW NOTES**
- 8040 XX ANODIZED ALUMINUM GLAZING: EXTERIOR LITE 3/16" MIN. TEMPERED GLASS OF SOLAR GRAY WITH A LITE TRANSMISSION FACTOR OF 46%. 1/4" ALUMINUM SPACER. INTERIOR LITE - 1/8" MIN. CLEAR TEMPERED. ALL OPERABLE SASH SHALL HAVE ALUMINUM SCREENS.

- FINISH NOTES**
- SUB-FLOOR PREP: PREPARATION FOR SUB FLOOR TO ACCEPT FINISH FLOORING IS BY FLOORING CONTRACTOR. PLYWOOD SUB FLOOR IS 2.4.1 PLYWOOD. OUTER PLY IS PLUGGED AND TOUCH SANDED, ANY DEFORMITIES DUE TO STANDARD CONSTRUCTION PRACTICES SHALL BE FILLED AND SANDED BY FLOORING CONTRACTOR. THE JOINT AT THE MODULE JOINING SHALL NOT BE LARGER THAN 1/8" AND SHALL BE FILLED AND SANDED BY FLOORING CONTRACTOR.

- HARDWARE SCHEDULE**
- HARDWARE SET #1**
- LOCKSET - SCHLAGE 070PD, WITH RHODES LEVER, OR EQUAL
 - BITS - 1-1/2" PAIR HAGER 1181 BB 4-1/2 x 4-1/2 NRP 260 DR EQUAL
 - CLOSER - MORTON 8800 DA / LCN 480 OR EQUAL
 - THRESHOLD - PEMCO 271A OR EQUAL
 - DOOR BOTTOM - PEMCO 218V OR EQUAL
 - WEATHERSTRIP - PEMCO 288W OR EQUAL
 - DOOR STOP - QUALITY #44 OR EQUAL
- HARDWARE SET #2**
- LOCKSET - SCHLAGE D53PD, WITH RHODES LEVER, OR EQUAL
 - BITS - 1-1/2" PAIR HAGER BB1278 4-1/2 x 4-1/2 260 OR EQUAL



PROJECT NUMBER: 4815 © MODTECH, INC. 1999

MOBILE MODULAR

DRAWN BY: CL DATE: 07/07/03

CHECKED BY: DATE:

REVISION NUMBER:

A6.02

REVISIONS

NO.	DESCRIPTION	DATE

Professional Engineer's Seal

Structural Engineer's Seal

Professional Engineer's Seal

Architect's Seal

REGISTERED ARCHITECT

STATE OF CALIFORNIA

PC-04

DATE: 7/2/03


MODTECH INC.

2830 BARRETT AVENUE
 PERRIS, CALIF. 92572

PH: (909) 943-4014
 FAX: (909) 940-0427

SCHEDULE SHEET

FILE PATH: 2440-0-AS-04W6 PROJECT NO: 4815



KEY NOTES


- 6 3/8 X 2 1/2 X 12GA. BLOCKING AT MIDSPAN OF JOIST
- 5" DIA (12 P)
- C 7X9 SEE 5
- PLYWOOD 1 1/8" THICK W/ 48" X 13' AT 8" O.C. SUPPORTED EDGES AND 6" O.C. FIELD TO JOIST. (TYPICAL) SEE 10/S2.2
- 6 3/8 X 2 1/2 X 12GA. FLOOR JOIST AT 48" O.C.
- TYPICAL BOLT HOLE LOCATION (SEE 2/S1.2)
- 1" HOLE @ MID-DEPTH FOR HANDLING

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023

NOTES

- FOR L HAND & R HAND FRAME SEE S1.0
- WELDING FIT-UP: OPENINGS = 1/2" OR 1/8" MIN FOR FULL PEN AND -t- t = BASE METAL THICKNESS

FILE PATH:



FLOOR FRAMING PLAN

FLOOR LIVE LOAD - 50 PSF









SCALE 1/4"=1'-0"

FLOOR JOIST TABLE

LIVE LOAD PSF	JOIST SPACING STANDARD	OPTIONAL UP GRADE TO STIFFEN FLOOR		
		0"	24"	18"
50	48"	-	-	-

OPTION 1 FLOOR PLAN: A1.1

					<p>2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427</p>	PROJECT NUMBER: 4815 MOBILE MODULAR	© MODTECH, INC. 2002 ALL RIGHTS RESERVED	DRAWN BY: GL DATE: 07/07/03 CHECKED BY: DATE:
<p align="center">FLOOR FRAMING PLAN</p>						<p align="center">S1.0</p>		



- KEY NOTES**
- 1 CAP CLOSURE AT RIDGE 26GA. GALV. W/ #10 TYPE FASTENERS W/NEOPRENE WASHERS TO RIB BOTH SIDES OF MODLINE. SET CAP IN SEALANT. BOTH SIDES.
 - 2 5/8" PL
 - 3 E.
 - 4 M
 - 5 14" (S)
 - 6 ST
 - 7 ROOF
 - 8 PLYWOOD FLOOR SHEATHING
 - 9 FLOOR JOIST SEE 6/S2.2
 - 10 FLOOR BEAM SEE 5/S2.2
 - 11 HAND HOLE AT BOLT LOCATION
 - 12 #14 STMS.
 - 13 3 1/2"x3 1/2"x1/4" STEEL TUBE COLUMN SEE 12/S2.2
 - 14 ROOF HEADER SEE 3/S2.2
 - 15 1/4" STIFFENER PLATE SEE 9/S2.2 FOR TYP. WELD
 - 16 SEALANT
 - 17 ROOF PURLIN SEE 2/S2.2
 - 18 3 1/4" X 1" X 45 11/16" LG X 10GA CHANNEL TOP AND BOTTOM OF OPENING

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
REVIEWED FOR

SS FLS STS ACS

DATE: 5/17/2023

~~IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE: 104-883
DATE: JUL 1 0 2003~~

~~IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE: 104-883
DATE: JUL 1 0 2003~~

MECHANICAL	MECHANICAL ENGINEER'S SEAL	MECHANICAL ENGINEER'S SEAL	PC PROFESSIONAL OF RECORD SEAL	ARCHITECT'S SEAL

MODTECH
2830 BARRETT AVENUE FAX (909) 943-4014
PERRIS, CALIF. 92572 FAX (909) 940-0427


PROJECT NUMBER: 4815
MOBILE MODULAR

© MODTECH, INC. 2002
ALL RIGHTS RESERVED


DRAWN BY: GL
DATE: 07/07/03
CHECKED BY: DVS
DATE: 07/07/03

S1.2


PROJECT NO. 4815




ROOF FRAMING PLAN - DUAL PITCH
SCALE: 1/4"=1'-0"




ROOF CAP AT MODLINE (ALTERN.) E




ROOF CAP AT 4' SEPARATION F




CROSS BRACING AT END WALL A



CROSS BRACING AT SIDE WALL B



ROOF FLASHING AT SIDE WALL C





ROOF STANDING BEAM D

KEY NOTES

- C 14 X 12GA. HEADER
- 6"x2 1/2"x14GA. ROOF PURLIN SEE PL
- 22GA. ROOF WITH SEA
- TAP SEE
- RID SEE
- 1/4" CONTINUOUS BEAD OF SEALANT AROUND ENTIRE PERIMETER OF FRAME
- 4"x2 1/2"x14 GA. FASCIA SEE 4/S2.2

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-120975 INC:
REVIEWED FOR
SS FLS STACS
DATE: 5/17/2023



REVISIONS	Author	Engineer's Seal	Material Engineer's Seal	PC Professional of Record Seal	Architect's Seal

PC
CBC 2001
MODTECH, INC.
2830 BARRETT AVENUE FAX (909) 943-4014
PERRIS, CALIF. 92572 FAX (909) 940-0427



PROJECT NUMBER: 4815
MOBILE MODULAR
ROOF FRAMING PLAN

MODTECH, INC. 2002
ALL RIGHTS RESERVED
DRAWN BY: DL
DATE: 07/07/03
CHECKED BY:
DATE:
W/FASCIA
S2.0


PROJECT NO. 4815
PC-04-104796

KEY NOTES


- 1 100A TAPERED RF. BM. SEE DETAIL #1 & #7
- 2 NOT IDENTIFICATION STAMP DIV. OF THE STATE ARCHITECT
- 3 APP: 01-120975 INC:
- 4 REVIEWED FOR
- 5 SS FLS ACS
- 6 DATE: 5/17/2023
- 7
- 8
- 9 #10 STSMS @ 6" O.C. (SEE S1.0)
- 10 PLYWOOD FLR. SHEATHING
- 11 FLOOR BEAM SEE DETAIL #5
- 12 NOT USED
- 13 6" X 2 1/2" X 14GA PURLIN
ALT: 4" X 3" X 12GA DETAIL #2
- 14 STIFFENER PLATE 3"x1/4" THICK AT 8'-0" OC



PURLIN AT INT. SIDE WALLS 13 PURLIN AT EXT. SIDE WALLS 11 BEAM SPLICE W/STIFFENER 9 FLOOR BEAM C7X9.8 5 TAPERED ROOF BEAM 1



CORNER COLUMN 12 FLR LOIST AT FLOOR BEAM 10 FLOOR JOIST 6 ROOF PURLIN 3" - 1'-0" 2





BM SPLICE - RIDGE (DUAL SLOPE) 7 ROOF HEADER 3

ENVELOPE	Structural Engineer's Seal	Mechanical Engineer's Seal	PC Professional of Record Seal	Architect's Seal

MODTECH
 2830 BARRETT AVENUE FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427

PROJECT NUMBER: 4815
 MOBILE MODULAR
 © MODTECH, INC. 2002 ALL RIGHTS RESERVED
 DRAWN BY: CL DATE: 07/07/03
 CHECKED BY: DATE:
S2.2



FILE PATH:

PROJECT NO. 4815

PC-04-10496

KEY NOTES



- 1 EN 10 GA. BACK-UP PLATE
- 2 2" X 1/4" STIFFENER ANGLE
- 3 6" X 3" X 1/2" X 1/4" STEEL PLATE WELDED FLUSH TO TOP AND BOTTOM OF CHANNEL FLANGES
- 4 6" X 3" X 1/2" X 1/4" COLUMN
- 5 SS FLS STACS
- 6 DATE: 5/17/2023
- 7 [10 GA. INFERRED ROOF BEAM (SEE 1/S2.2) OR 12/S2.2 REFER TO RF. FRAMING PLAN
- 8 I.S. 3 1/2" X 3 1/2" X 1/4" COLUMN
- 9 BACK-UP PLATE MIN. 10 GA.
- 10 [7X0.8 FLOOR CHANNEL
- 11 3 1/2" X 3 1/2" X 1/4" STEEL PLATE WELDED FLUSH TO TOP AND BOTTOM OF CHANNEL FLANGES
- 12 NOT USED
- 13 3 1/2" X 3 1/2" X 1/4" STIFFENER ANGLE COPE TO FIT C7 X 9.8
- 14 STIFFENER TS 3 1/2" X 3 1/2" X 1/4"
- 15 [14" X 3 1/2" X 1/2" X 1/4" HEADER (SEE 3/S2.2)
- 16 LOCATION OF HVAC OPENING
- 17 3" X 3" X 1/4" THICK X 1/2" LONG INSERT POST
- 18 1/4" FULL DEPTH STIFFENER PLATE AT 4'-0" OC AT EXTERIOR SIDEWALLS ONLY FOR 80 MPH DESIGN WIND LOAD ONLY
- 19 1/4" BASE PLATE-INSERT FLUSH WITH STIFFENER TUBE
- 20 (1) 3" X 3" X 10 GA TUBE STEEL BACK-UP TUBE OR (4) 10 GA BACK-UP PLATES

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
REVIEWED FOR
















SS FLS STACS

DATE: 5/17/2023



10 SECTION AT SIDEWALL

B SECTION AT ENDWALL A



REVISIONS	Checked _____	Engineer's Seal	Mechanical Engineer's Seal	PC Professional of Record Seal	Architect Seal	PROJECT NUMBER: 4815	MODTECH, INC. 2002	DATE: 07/07/03
						MOBILE MODULAR		DATE:
						STRUCTURAL ELEVATIONS W/ FASCIA		S3.0

MODTECH



2830 BARNETT AVENUE
PERRIS, CALIF. 92571

PH (909) 943-4014
FAX (909) 940-0427


PROJECT NO. 4815

KEY NOTES


- 1 4 X 4 POST,ALT,USE 2-2X4 W/FACE NAILING
- 2 2X4 TOP PLATE
- 3 IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
- 4 APP: 01-120975 INC:
- 5 REVIEWED FOR
- 6 SS FLS RES ACS
- 7 DATE: 5/17/2023
- 8
- 9 A 3/4" CLIPS AT HEADERS & SILL TO FULL HGT. STUDS AND FULL HGT. STUDS TO TOP AND BOTTOM PLATES.SEE 4/S5.0
- 10 REQUIRED OPENING FOR A 3068 DOOR (SEE DETAIL 7/S5.0)
- 11 REQUIRED OPENING FOR A 8040 WINDOW (SEE DETAIL 6/S5.0)
- 12 2X4 STUD AT 16" O.C. TYPICAL
- 13 2X4 NAILER TYPICAL AT EACH END
- 14 2X4 SILL PLATE
- 15 FRAME FOR ELECTRICAL PANEL
- 16 THERMOSTAT LOCATION 4S BOX
- 17 2" X 4" BLOCKING AT EXTERIOR PLYWOOD SIDING JOINT




A




B



C





D



E


SCALE 3/8"=1'



FILE PATH

PROJECT NO. 4815

REVISIONS	MECHANICAL ENGINEER'S SEAL	MECHANICAL ENGINEER'S SEAL	PROFESSIONAL OF RECORD SEAL	ARCHITECT'S SEAL



MODTECH
 2830 BARRETT AVENUE FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427

PROJECT NUMBER: 4815
 MOBILE MODULAR

MODTECH, INC. 2002
 ALL RIGHTS RESERVED


DRAWN BY: DL
 DATE: 07/07/03
 CHECKED BY:
 DATE:

WALL FRAMING

WOOD STUDS

S4.0


NAILING SCHEDULE	
CONNECTION	NAILING
1. JOIST TO WALL OR BRACKETING	2-10d
2. JOIST TO JOIST	2-10d
3. JOIST TO STUD	2-10d
4. STUD TO STUD	2-10d
5. STUD TO JOIST	2-10d
6. STUD TO LAMB OR BRACKET	2-10d
7. STUD TO STUD	2-10d
8. STUD TO STUD	2-10d
9. STUD TO STUD	2-10d
10. STUD TO STUD	2-10d
11. STUD TO STUD	2-10d
12. STUD TO STUD	2-10d
13. STUD TO STUD	2-10d
14. STUD TO STUD	2-10d
15. STUD TO STUD	2-10d
16. STUD TO STUD	2-10d
17. STUD TO STUD	2-10d
18. STUD TO STUD	2-10d
19. STUD TO STUD	2-10d
20. STUD TO STUD	2-10d
21. STUD TO STUD	2-10d
22. STUD TO STUD	2-10d
23. STUD TO STUD	2-10d
24. STUD TO STUD	2-10d
25. STUD TO STUD	2-10d




OPENING	HDR.	SILL	JAMB	HEIGHT	WIDTH
3068	(2) 2X4	(2) 2X4	(2) 2X4 *	81 1/4"	36"
8040	(3) 2X4	(2) 2X4	(3) 2X4 *	48 1/8"	68 1/8"

* FULL HEIGHT STUDS


ALTERNATE: METAL STUD 3 1/2" X 20 GA. IN LIEU OF 2X4 WD. STUDS




9 WINDOW SILL AT JAMB




5 DETAIL AT VERT. PLYWOOD EDGES




10 TYP. WINDOW FRAMING




6 DETAIL AT HORIZ. PLYWOOD JOISTS



11 TYP. DOOR FRAMING



7 SECTION AT STUD



8 HEADER DETAIL

12 ROUGH OPENING SCHEDULE

KEY NOTES

- EXTERIOR PLYWOOD SIDING - SHEATHING NAIL W/GALV. BOX NAILS - 8d AT 6" O.C. EDGES, 8d AT 12" O.C. IN FIELD
- GYP. BOARD
- TYP. INTERIOR
- E.N.
- 2X4 BLK'
- "2" FLASHING
- 2X4 AT
- WATERPROOF
- HEADER (S)
- INSULATION
- 8d ELECTRO GALV. NAILS
- 2X4 SILL PLATE (BELOW)
- FULL HEIGHT STUDS AND 1-2X4 TRIMMER (SEE OPENING SCHEDULE FOR JAMB STUDS REQ'D FOR DOORS & WINDOWS ONLY)
- SILL PLATE (SEE SCHEDULE)
- 2X4 FULL HEIGHT KING STUDS AND 2X4 TRIMMER (SEE SCHEDULE FOR QUANTITY)
- A 34 CLIPS AT HEADER AND SILL TO FULL HEIGHT STUDS AND FULL HEIGHT STUDS TO TOP AND BOTTOM PLATES
- 9GA 8d 1 1/2" NAILS
- LAP JOINT
- 2" WIDE DUCT SUPPORT STRAP @ 48" O.C.
- PLENUM
- DUCTWORK
- ROOF PURLIN
- TRANSFER BOX
- ROOF CHANNEL
- 18D @ 16" O.C.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS STACS
 DATE: 5/17/2023

NOTES

- NAILING:
 -NAILING IN ACCORDANCE W/ T.24 C.A.C. TABLE 2-25 P
 -ALL NAILS EXPOSED TO WEATHER SHALL BE GALV.
 -MACHINE APPLIED NAILING SHALL HAVE PRIOR DEMONSTRATION AND APPROVAL BY O.S.A. / OSA FIELD REP. AND THE ARCHITECT.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 PROJECT NO. 4815
 DATE: JUL 07 2003

PROJECT NUMBER: 4815
 MODTECH, INC. 2002 ALL RIGHTS RESERVED
 MOBILE MODULAR
 DRAWN BY: OL DATE: 07/07/03
 CHECKED BY: DATE:
 S5.0

NO.	REVISION	DATE

Professional Engineer's Seal
 Mechanical Engineer's Seal
 PC Professional of Record Seal
 Architect's Seal

PC
 CBC 8001
 10/2003

MODTECH
 2830 BARRETT AVENUE . FAX (909) 943-4014
 PERRIS, CALIF. 92572 FAX (909) 940-0427




FRAMING DETAILS

WOOD STUDS

FILE PATH: PROJECT NO. 4815

KEY NOTES

- 1 22 GA. MET. ROOF DECK
- 2 IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
- 3 APP: 01-120975 INC:
- 4 REVIEWED FOR
- 5 SS FLS ACS
- 6 DATE: 5/17/2023
- 7
- 8 2X4 STUDS @ 16" O.C.
- 9 16d BOX NAILS @ 8" O.C.
- 10 2X4 SILL PLATE.
- 11 2X TRIMMER @ CORNER.
- 12 16d @ 24" O.C.
- 13 #10 S.T.S.M.S @ 16" O.C. OR AEROSMITH
#144.0175 DRIVE PIN.
- 14 2X4 TRIM
- 15 ROOF BEAM
- 16 PROVIDE VAPOR BARRIER OVER INSULATION AT
CEILING AND ROOF BEAMS
- 17 1/2" SHM



NO.	REVISION

Professional Engineer's Seal	Professional Engineer's Seal	Professional Engineer's Seal	Professional Engineer's Seal

PC
CBC 2001
10/7/20

MODTECH
2030 BARRETT AVENUE FAX (909) 943-4014
PERRIS, CALIF. 92572 FAX (909) 940-0427

PROJECT NUMBER: 4815
MOBILE MODULAR

© MODTECH, INC. 2002
ALL RIGHTS RESERVED

FRAMING DETAILS


WOOD STUDS

DRAWN BY: CL
DATE: 07/07/03


CHECKED BY:
DATE:

S5.2


PROJECT NO. 4815



MECHANICAL (HVAC) PLAN
OPTION-1
 (24'x40')
 SCALE: 1'-0"



MECHANICAL (HVAC) PLAN
OPTION-2
 (24'x40')
 SCALE: 1'-0"



PLENUM DIMENSIONS 3

KEY NOTES

- 1 WALL MOUNT 4 TON HEAT PUMP WITH 50W HEATER OLA AND CALIFORNIA STATE ENERGY APPROVED 208/230V, 1 PHASE, 28 AMP WEIGHT 615 LBS-12 REER
- 2 THERMOSTAT AT 48" AFF (SEE SCHEDULE)

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:
 REVIEWED FOR

SS FLS ACS


DATE: 5/17/2023

NOTES

1. INSULATION APPLIED TO EXTERIOR SURFACE OF DUCTS LOCATED IN BLDGS SHALL HAVE A FLAME SPREAD OF NOT MORE THAN 25 AND A SMOKE-DEVELOP NOT EXCEEDING 80 WHEN TESTED AS A COMPOSITE INSTALLATION, INCLUDING INSULATION, FACING MATERIALS, TAPES AND ADHESIVES AS NORMALLY APPLIED
2. SCHOOL EQUIPMENT ANCHORAGE
 THE FOLLOWING IS FOR THE MECHANICAL ENGINEER'S INFORMATION ONLY:
 THE BEARING ANCHORAGE OF MECHANICAL EQUIPMENT SHALL CONFORM WITH TITLE 24, SECTION 12000 AND TABLE 120.0. ANCHORAGE DETAILS FOR ROOF/FLOOR BEARING EQUIPMENT WEIGHING LESS THAN 400 LBS AND HANGING EQUIPMENT WEIGHING LESS THAN 20 LBS, MAY BE OMITTED FROM THE PLANS.
 ALL MECHANICAL EQUIPMENT SHALL BE SPACED OR ANCHORED TO RESIST A HORIZONTAL FORCE ACTING IN ANY DIRECTION UNDER THE FOLLOWING CRITERIA:
 EQUIPMENT ON ROOF: 33% OF OPERATING WEIGHT
 EQUIPMENT ON STRUCTURE: 40% OF OPERATING WEIGHT
 FOR FLEXIBLY MOUNTED EQUIPMENT USE 4 TIMES THE ABOVE VALUES AND FOR SIMULTANEOUS WINDL FORCE USE 1/3 TIMES THE HORIZONTAL FORCE.
 THE ABOVE VALUES ARE FOR AN IMPORTANCE FACTOR, I = 1.0 AND SEISMIC ZONE, Z = 4
 WHERE ANCHORAGE DETAILS ARE NOT SHOWN ON THE DRAWINGS THE FIELD INSTALLATION SHALL BE SUBJECT TO THE APPROVAL OF THE MECHANICAL ENGINEER AND THE FIELD ENGINEER OF THE OFFICE OF THE STATE ARCHITECT.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 OFFICE OF THE STATE ARCHITECT
 04-10-2003
 JUL 9 2003

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 OFFICE OF THE STATE ARCHITECT
 04-10-2003
 JUL 9 2003



THERMOSTAT ACCESS 1

<p>REVISIONS</p> <table border="1"> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table>																					<p>Division Engineer's Seal</p>	<p>Mechanical Engineer's Seal</p>	<p>PC Professional of Record Seal</p>	<p>Architect's Seal</p>	<p>PROJECT NUMBER: 4815 MOBILE MODULAR</p>	<p>© MODTECH, INC. 2002</p>	<p>DRAWN BY: DL DATE: 07/07/03 CHECKED BY: DATE:</p>
<p>MODTECH 2830 BARRETT AVENUE PERRIS, CALIF. 92571 PH (909) 943-4014 FAX (909) 940-0427</p>					<p>MECHANICAL (HVAC) PLAN 4 TON M1.0</p>																						

PROJECT NO. 4815
 PC-04-104798

ELECTRICAL PANEL SCHEDULE

PANEL	LOAD	WATTS		AMPS		VOLTS	SINGLE #	THREE WIRE
		A	B	A	B			
RECEPTACLE	1000	20	1	2	2	120/240	1	
RECEPTACLE/CLOCK	4500	20	1	2	2	120/240	1	
HEAT STRIPS (DKW)	3120	20	1	2	2	120/240	1	
INT/EXT LIGHTS	600	20	1	2	2	120/240	1	
FIRE ALARM (DEDICATED)	500	20	1	2	2	120/240	1	
TOTAL	18840	77	3	6	6	120/240	3	THREE WIRE

GENERAL GROUNDING NOTES

- EACH BUILDING SHALL BE SEPARATELY GROUNDED WITH A 3/4" RD. X 8" COPPER/ALUM. STEEL GROUND ROD. WHERE ROCK BOTTOM IS ENCOUNTERED, ROD SHALL BE DRIVEN AT AN ANGLE NOT TO EXCEED 45 DEGREES FROM THE VERTICAL OR SHALL BE BURIED IN A TRENCH THAT IS AT LEAST 30" DEEP (BY SITE ELECTRICAL).
- TESTING: TEST FOR RESISTANCE TO GROUND. IF RESISTANCE EXCEEDS 25 OHMS, INSTALL ADDITIONAL GROUND RODS SEPARATED AT LEAST 6'-0" UNTIL RESISTANCE IS REDUCED TO 25 OHMS OR LESS. (BY SITE ELECTRICAL).
- APPROVAL OF THIS PLAN DOES NOT CONSTITUTE APPROVAL OF THIS FIRE ALARM FOR ALL SITES. THE FIRE ALARM SYSTEM AND/OR COMPONENTS MUST BE DESIGNED TO BE COMPATIBLE TO SITE LOCATION, EXISTING CONDITIONS OR INCOMPATIBLE COMPONENTS.
- GROUNDING TEST SHALL BE DONE IN THE PRESENCE OF THE PROJECT INSPECTOR. ALL GROUNDING SHALL BE IN ACCORDANCE WITH CEC ARTICLE 250.

ELECTRICAL LEGEND

-
-
-
-
-
-
-
-
-
-
-
-
-
-
-


IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 01-120975 INC:


REVIEWED FOR

SS FLS ACS

DATE: 5/17/2023




OPTION-1




OPTION-2

ELECTRICAL PLAN (24'x40')
SCALE: 1"=0'



TYP GROUNDING DETAIL 1



GROUND JUMPER - MOD LINE 2

NOTES

- SCHOOL EQUIPMENT ANCHORAGE
THE FOLLOWING IS FOR THE ARCHITECT'S INFORMATION ONLY:
THE SEISMIC ANCHORAGE OF ELECTRICAL EQUIPMENT SHALL CONFORM TO CEC TITLE 24, SECTION 18000 FOR TABLE 18000-2. ANCHORAGE DETAILS FOR ROOF/FLOOR MOUNTED EQUIPMENT WEIGHING LESS THAN 400 LBS & HUNG EQUIPMENT WEIGHING LESS THAN 20 LBS MAY BE OMITTED FROM THE PLANS.
FOR ELECTRICAL DRAWINGS:
ALL ELECTRICAL EQUIPMENT SHALL BE BRACED OR ANCHORED TO RESIST A HORIZONTAL FORCE ACTING IN ANY DIRECTION USING THE FOLLOWING CRITERIA:
EQUIPMENT ON GROUND: 50% OF OPERATING WEIGHT
EQUIPMENT ON STRUCTURE: 40% OF OPERATING WEIGHT
FOR FLOOR MOUNTED EQUIPMENT USE 4 TIMES THE ABOVE VALUES, AND FOR SIMULTANEOUS VERTICAL FORCE USE 1/3 TIMES THE HORIZONTAL FORCE.
THE ABOVE VALUES ARE FOR AN IMPORTANCE FACTOR, I = 1.0 AND SEISMIC ZONE, 2 = 4
WHERE ANCHORAGE DETAILS ARE NOT SHOWN ON THE DRAWINGS THE FIELD INSTALLATION SHALL BE SUBJECT TO THE APPROVAL OF THE ARCHITECT AND THE FIELD ENGINEER OF THE OFFICE OF THE STATE ARCHITECT.

 MODTECH, INC. 2830 BARRETT AVENUE FAX (909) 943-4014 PERRIS, CALIF. 92572 FAX (909) 940-0427			PROJECT NUMBER: 4815 MOBILE MODULAR © MODTECH, INC. 2002 ALL RIGHTS RESERVED DATE: 07/07/03 CHECKED BY: [Signature] E1.03		

PROJECT NO. 4815
PC-04-109756



$S_s = 2.183$ (MAPPED VALUE)

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-120975 INC:
REVIEWED FOR:
SS FLS ACS
DATE: 5/17/2023

PRE-CHECK (PC) DOCUMENT
CODE: 2019 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

MOBILE MODULAR MANAGEMENT
11450 MISSION BLVD.
MIRA LOMA, CA 91752

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-119396 PC
REVIEWED FOR:
SS FLS ACS CG
DATE: 10/29/2020




FOUNDATION PLAN - 50 PSF FLOOR LIVE LOAD + 20 PSF PARTITIONS

FOUNDATION PLAN - 50 PSF FLOOR LIVE LOAD

TIE PLATE SCHEDULE: (1) (2) (3) 50 PSF / 50 + 20 PSF $S_s = 2.183$			TIE PLATE SCHEDULE: (1) (2) (3) 50 PSF / 50 + 20 PSF $S_s = 2.183$ AMERICAN MODULAR SYSTEMS, INC.			SHOT PIN SCHEDULE: 50 PSF / 50 + 20 PSF $S_s = 2.183$ AMERICAN MODULAR SYSTEMS, INC.		
Building Size	NUMBER OF TIE PL'S PER ENDWALL	NUMBER OF TIE PL'S PER SIDEWALL	Building Size	NUMBER OF TIE PL'S PER ENDWALL	NUMBER OF TIE PL'S PER SIDEWALL	Building Size	NUMBER OF SHOT PINS PER ENDWALL	SHOT PINS PER SIDEWALL
24'x40'	4	4	24'x40'	9	9	24'x40'	19" O.C.	32" O.C.
36'x40'	6	6	36'x40'	7	7	36'x40'	19" O.C.	24" O.C.
48'x40'	12	12	48'x40'	9	9	48'x40'	19" O.C.	16" O.C.

(1) SEE DETAIL 7/F-6 FOR TYPICAL TIE PLATE
(2) USE THE PLATES FOR ALL MODULAR BUILDING MANUFACTURERS EXCEPT AMERICAN MODULAR
(3) SEE DETAIL 8/F-6 FOR THE PLATE APPLICABLE TO AMERICAN MODULAR SYSTEMS, INC.

- NOTES:
- SEE SHEET F-1 FOR GENERAL NOTES.
 - SEE SHEET F-7 FOR TYPICAL NOTES.
 - UNDER FLOOR VENTILATION: (@24'x40' BLDG.)*
REQUIRED VENT. AREA = $24' \times 40' / 150 = 6.4$ SQ. FT.
MIN. VENT. AREA PROVIDED = $0.25' \times (4 \times 4 + 4 \times 3.385) = 7.38$ SQ. FT. (OK)
 - UNDER FLOOR VENTILATION: (@36'x40' BLDG.)*
REQUIRED VENT. AREA = $36' \times 40' / 150 = 9.6$ SQ. FT.
MIN. VENT. AREA PROVIDED = $0.375' \times (6 \times 4 + 4 \times 3.387) = 14.08$ SQ. FT. (OK)
 - UNDER FLOOR VENTILATION: (@48'x40' BLDG.)*
REQUIRED VENT. AREA = $48' \times 40' / 150 = 12.8$ SQ. FT.
MIN. VENT. AREA PROVIDED = $0.375' \times (8 \times 4 + 4 \times 3.385) = 17.08$ SQ. FT. (OK)
 - PROVIDE 2-2X PLATES OR BLOCKS @ 24'x40' BUILDING (MIN. HEIGHT = 3")
PROVIDE 3-2X PLATES OR BLOCKS @ 36' & 48'x40' BUILDINGS (MIN. HEIGHT = 4 1/2")
 - ALLOWABLE SOIL BEARING = 1000 PSF, PER DSA I.R.16-1
 - ALL NAILS FOR PLATE TO PLATE NAILING SHALL BE 16d GALV. BOX.
ALL NAILS FOR PLYWOOD SKIRTING SHALL BE 8d GALV. BOX.
ALL FOUNDATION NAILS SHALL BE HOT DIPPED GALVANIZED WITH A MIN. OF 1 OZ. OF ZINC PER SQ. FT.
 - UNDERFLOOR DRAINAGE SHALL BE PROVIDED TO PREVENT WATER FROM PONDING BENEATH THE STRUCTURE. UNDERFLOOR DRAINAGE SHALL BE NOTED AND DETAILED ON THE PROJECT SPECIFIC SITE PLANS.
 - HEIGHT OF BUILT UP PLATES WITH SILL PLATE IS NOT TO EXCEED 18" MAX.
 - ALL 2X PLATES AT EXTERIOR FOUNDATIONS AND 2X6 PLATES AT MODLINES TO BE 4' OR 8' LONG WITH NO SPLICES. IF SHORTER PIECES OF 2X PLATES ARE TO BE USED, SPLICE PLATES PER DETAIL 9/F-6.
- * NOTE: UNDER FLOOR VENTILATION CALCULATION BASED ON 3" OR 4 1/2" HIGH VENTS. CALCULATIONS CAN VARY BASED ON ACTUAL SITE GRADE ELEVATIONS AND VENT HEIGHTS. MIN. VENT HEIGHT = 1 1/2" AND MAX. VENT HEIGHT = 16 1/2". PROVIDE NOTED REQUIRED VENT. AREA FOR EACH SIZE BUILDING.

SITE SPECIFIC APPROVAL	DSA PC STAMP PRE-CHECK (PC) DOCUMENT CODE: 2019 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED	APPROVAL - PC ENGINEER OF RECORD  Date Signed: September 24, 2020
------------------------	--	--

MEMBER
STRUCTURAL ENGINEERS ASSOCIATION OF CALIFORNIA
AMERICAN CONCRETE INSTITUTE
(909) 613-0234
Fax (909) 613-0238

EXL
STRUCTURAL ENGINEERS, INC.
4091 RIVERSIDE DRIVE, SUITE 114
CHINO, CALIFORNIA 91710

This drawing and the material contained therein are the property of Mobile Modular Management Corporation (MMC) and shall not be reproduced, copied or otherwise disposed of directly or indirectly and shall not be used in whole or in part to assist in the making of, or for the purpose of furnishing, any information for the making of drawings, prints, apparatus or parts thereof without the full knowledge and written consent of MMC and all patentable material contained herein and originating with MMC and shall be the property of MMC.

TABLE OF CONTENTS			
Sheet No	Description	Dated	Revised

DRAWN
CHECKED
DATE
AUG. 15, 2020
SCALE
JOB NO.
F-3
OF 19 SHEETS

PC 04-119396
FOUNDATION PLANS

















IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023

PRE-CHECK (PC) DOCUMENT
 CODE: 2019 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

MOBILE MODULAR MANAGEMENT
 11450 MISSION BLVD.
 MIRA LOMA, CA 91752

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-119396 PC
 REVIEWED FOR
 SS FLS ACS CG
 DATE: 10/29/2020

PC 04-119396
 DETAILS



- NOTES:
 1. EXTERIOR SKIRTING VENTS
 • PROTECTED BY CORROSION-RESISTANT, NONCOMBUSTIBLE WIRE MESH WITH OPENING 1/16" TO 1/8"
 • MEETS CBC CHAPTER 7A-706A.2 REQUIREMENTS VENTS - REQUIREMENTS #1 & #2
 • CAL-FIRE "LISTING NUMBER" 8165-2192.0100; 8165-2214.0100; 8165-2232.0500 OR EQUIVALENT
 2. EXTERIOR SKIRTING (FLOOR LINE TO GRADE)
 • 19/32"x4"x9" ROSEBURG DURATEMP SLIDING (UN-GROOVED OR GROOVED @ 8" O.C.)
 • MEETS APA 303 SPECIFICATIONS FOR PLYWOOD SLIDING
 • COMPLIES WITH SEM 12-7A-1
 • CAL-FIRE "LISTING NUMBER" 8140-2031.0004
 • MEETS CBC CHAPTER 7A-707A.3.1 "EXTENT OF EXTERIOR WALL COVERING"
 • MATERIAL USED SAME AS EXTERIOR SIDING TO MEET WUI REQUIREMENTS

NOTE: PC NOT USEABLE IN WILDLAND URBAN INTERFACE (WUI) AREAS. SEE DETAIL 11 FOR WUI ARE REQUIREMENTS

NOTE: ATTACH PLYWOOD SKIRTING TO CONT. TOP PLATE AND TO PLATES/BLOCKING W/ 8d GALVANIZED BOX NAILS (ELECTRO PLATED, TUMBLE COATED OR HOT DIPPED) @ 6" O.C. FN. SKIRTING IS NON-STRUCTURAL.

NOTE: PC NOT USEABLE IN WILDLAND URBAN INTERFACE (WUI) AREAS. SEE DETAIL 11 FOR WUI ARE REQUIREMENTS

SITE SPECIFIC APPROVAL	DSA PC STAMP	APPROVAL - PC ENGINEER OF RECORD	MEMBER	TABLE OF CONTENTS			
	PRE-CHECK (PC) DOCUMENT CODE: 2019 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED		STRUCTURAL ENGINEERS ASSOCIATION OF CALIFORNIA	Sheet No	Description	Dated	Revised
			AMERICAN CONCRETE INSTITUTE				
			(909) 613-0234 Fax(909) 613-0238				



Date Signed: September 24, 2020

EXL
 STRUCTURAL ENGINEERS, INC.
 4091 RIVERSIDE DRIVE, SUITE 114
 CHINO, CALIFORNIA 91710

This drawing and the material contained therein are the property of Mobile Modular Management Corporation (MMC) and shall not be reproduced, copied or otherwise disposed of directly or indirectly and shall not be used in whole or in part to assist in the making of, or for the purpose of furnishing, any information for the making of drawings, prints, apparatus or parts thereof without the full knowledge and written consent of MMC and all patentable material contained herein and originating with MMC and shall be the property of MMC.

DRAWN	CHECKED	DATE	SCALE	JOB NO.
		AUG. 15, 2020		

F - 6
 OF 19 SHEETS

GENERAL SPECIFICATIONS

SECTION 1A

1. GENERAL

A. THE REQUIREMENTS OF THE GENERAL CONDITIONS OF THE AGREEMENT AND THIS GENERAL REQUIREMENTS APPLY TO THE SEVERAL TRADE SECTIONS WITH THE SAME FORCE AS THOUGH FULLY REPEATED IN EACH SECTION.

B. NAME BRANDS ARE INDICATED TO ESTABLISH A STANDARD OF QUALITY. ITEMS OF EQUAL OR BETTER QUALITY MAY BE SUBSTITUTED FOR THE LISTED BRAND NAMED PRODUCTS.

2. SCOPE OF WORK

A. THE WORK CONSISTS OF MANUFACTURING OFF-SITE IN A PLANT, AND INSTALLING ON-SITE, MODULAR RELOCATABLE BUILDING AS DEFINED HEREIN AND SHOWN AND DETAILED ON DRAWINGS.

B. ALL REQUIREMENTS OF TITLE 19 AND 24 OF THE STATE OF CALIFORNIA CODE OF REGULATIONS (CCR) RELATING TO INSPECTIONS AND VERIFIED REPORTS SHALL BE COMPLIED WITH AND SHALL INCLUDE:

1. GENERAL RESPONSIBLE CHARGE OF FIELD ADMINISTRATION BY THE ARCHITECT OF RECORD.

2. INSPECTION DURING THE COURSE OF CONSTRUCTION BY AN INSPECTOR APPROVED BY THE DIVISION OF THE STATE ARCHITECT AND THE DISTRICT ARCHITECT. THE INSPECTOR SHALL BE RESPONSIBLE FOR AND APPROVED TO INSPECT THE GENERAL CONSTRUCTION, WELDING, MECHANICAL AND ELECTRICAL WORK. COST OF THESE INSPECTIONS SHALL BE BORNE BY THE SCHOOL DISTRICT.

3. ON SITE INSPECTION OF THE BUILDING INSTALLATION ELECTRICAL AND UTILITY OF THE BUILDING INSTALLATION BY AN INSPECTOR APPROVED BY THE DIVISION OF THE STATE ARCHITECT AND RETAINED BY THE SCHOOL DISTRICT.

4. OTHER SPECIAL TESTS OR INSPECTIONS AS MAY BE REQUIRED BY THE DIVISION OF THE STATE ARCHITECT. COST OF THESE INSPECTIONS/TESTS SHALL BE BORNE BY THE SCHOOL DISTRICT.

3. WORK NOT INCLUDED

A. ALL ON-SITE OR OFF-SITE UTILITIES AND THE CONNECTION OF THEM TO THE BUILDING UNLESS INDICATED ON THE DRAWINGS.

B. ALL LEVELING, GRADING OR OTHER SITE PREPARATION EXCEPT CONCRETE OR WOOD LEVELING STRIPS, WHERE REQUIRED, UNLESS OTHERWISE INDICATED ON THE DRAWINGS.

C. FIRE ALARM SYSTEM, FIRE EXTINGUISHER, PROGRAM BELL, CLOCK, PUBLIC ADDRESS SYSTEM, INTERCOM SYSTEM, TV SYSTEM UNLESS OTHERWISE INDICATED ON THE DRAWINGS.

4. WHEELS AND HITCH

SHALL REMAIN THE PROPERTY OF THE CONTRACTOR.

5. ACCESSIBILITY OF SITE

THE SCHOOL DISTRICT SHALL PROVIDE ACCESS TO THE SITE FOR THE INSTALLATION OF THE BUILDING. REMOVAL OF TREES, SHRUBS, FENCING, SPRINKLERS, ETC. NECESSARY FOR MOVE-IN AND REMOVAL OF BUILDINGS SHALL BE THE RESPONSIBILITY OF THE SCHOOL DISTRICT.

SECTION 2A SITE ASSEMBLY

1. SCOPE OF WORK

CONTRACTOR SHALL PROVIDE ALL LABOR, MATERIALS AND SERVICES TO PREPARE THE BUILDING ELEMENTS, TRANSPORT THEM FROM THE PLANT TO THE SITE AND TO COMPLETE THE ASSEMBLY AT THE SITE.

THE CONDITION OF THE SITE, SUCH AS DRAINAGE AND SOIL BEARING CAPACITY, SHALL BE THE RESPONSIBILITY OF THE SCHOOL DISTRICT.

2. ASSEMBLY OF ELEMENTS

A. THE ELEMENTS SHALL BE BROUGHT TO THE SITE ON WHEEL ASSEMBLY AND TRANSFERRED TO THE PREPARED SITE. GREAT CARE SHALL BE TAKEN TO AVOID DAMAGE TO THE ELEMENTS BY RACKING OR BUMPING.

B. CONNECTION OF THE ELEMENTS TOGETHER SHALL BE DONE ACCORDING TO INSTRUCTIONS ON THE DRAWINGS. FLASHING, TRIM AND OTHER LOOSE ITEMS SHALL BE INSTALLED PER PLANS AND DETAILS OF THE ORIGINAL MANUFACTURER'S DRAWINGS.

SECTION 3A CARPENTRY

1. SCOPE OF WORK

CONTRACTOR SHALL PROVIDE ALL LABOR, MATERIALS AND SERVICES TO INSTALL CARPENTRY.

2. WORKMANSHIP

A. FRAMING- SECURELY NAILED, BRIDGED AND BLOCKED TO FORM RIGID STRUCTURE. WORK CUT, FITTED AND ASSEMBLED LEVEL, PLUMB AND TRUE TO LINE. TRIM IN AS LONG LENGTHS AS POSSIBLE WITH ALL STANDING TRIM IN ONE PIECE. TRIM SEALED AT ALL EDGES.

B. NAILING- IN ACCORDANCE WITH TITLE 24 COR- TABLE 2304.10.1. NAILS SHALL BE CORROSION RESISTANT BOX NAILS.

C. MACHINE APPLIED NAILING- SHALL HAVE PRIOR DEMONSTRATION AND APPROVAL BY DSA FIELD INSPECTOR AND THE ARCHITECT. THE APPROVAL IS SUBJECT TO CONTINUES SATISFACTORY PERFORMANCE. PLYWOOD SHALL HAVE A MINIMUM THICKNESS OF 3/8" IF NAILHEADS PENETRATE THE OUTER PLY MORE THAN WOULD BE NORMAL FOR A HAND HAMMER OR IF MINIMUM ALLOWABLE EDGE DISTANCES ARE NOT MAINTAINED, THE PERFORMANCE WILL BE DEEMED UNSATISFACTORY.

D. TRIM SEALED AT ALL EDGES. SEALANT PAINTED TO MATCH TRIM OR SIDING.

SECTION 4A MATERIAL SPECIFICATIONS

1. STRUCTURAL FRAMING SHALL BE HEM FIR - GRADED IN ACCORDANCE WITH THE STANDARD GRADING RULES OF THE WESTERN WOOD PRODUCTS ASSOCIATION OR STANDARD GRADING RULES NO. 16 OF THE WEST COAST LUMBER INSPECTION BUREAU, LATEST EDITIONS. GRADES SHALL BE AS FOLLOWS UNLESS NOTED OTHERWISE ON THE DRAWINGS. (HEM FIR SOUTH IS NOT ALLOWED.) EACH PIECE SHALL BE GRADE MARKED AND NO PIECE MAY FALL BELOW GRADES INDICATED.

2. ALL FRAMING EXCEPT AS NOTED HEM FIR NO. 2. PLYWOOD SHALL BE AS SHOWN ON THESE DRAWINGS WITH EXTERIOR GLUE IN ACCORDANCE WITH U.S. PRODUCT STANDARD DOC PS 1-07 OR DOC PS-04.

ALL PANELS SHALL BE MARKED WITH AN APA GRADE MARK WITH AN IDENTIFICATION INDEX AS SHOWN ON DRAWINGS. USE 4'x8' PANELS, MINIMUM, EXCEPT AT BOUNDARIES AND FRAMING CHANGES WHERE MINIMUM PANEL DIMENSION SHALL BE 24" AT ROOFS AND FLOORS AND 12" AT WALLS.

3. BOLTS FOR TIMBER CONNECTIONS SHALL CONFORM TO ANSI/ASME STANDARD B18.2.1-2012 AND 2015 EDITION OF THE NDS. BOLTS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF OF THE LATEST EDITION OF THE NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION BY THE NATIONAL FOREST PRODUCTS ASSOCIATION (NDS). BOLT HOLES SHALL BE 1/32 TO 1/16 INCH LARGER THAN BOLT DIAMETER. RE-TIGHTEN BOLTS BEFORE CLOSING IN WORK. BOLTS SHALL BE FULL BODY STEEL BOLTS WITH MINIMUM YIELD STRENGTH OF 45,000 PSI.

4. LAG SCREWS SHALL BE STEEL AND CONFORM TO ANSI/ASME STANDARD B18.2.1 AND THE REQUIREMENTS OF THE 2015 NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION (NDS). HOLES FOR LAG SCREW SHANKS SHALL BE BORED THE SAME DEPTH AND DIAMETER AS THE SHANK. THE REMAINING DEPTH OF PENETRATION OF THE SCREW SHALL BE BORED TO 70% OF THE SHANK DIAMETER. ONE QUARTER INCH (1/4") DIAMETER LAG SCREWS NEED NOT HAVE PRE-DRILLED HOLES IF IT CAN BE SHOWN THAT THE WOOD MEMBERS ARE NOT DAMAGED DURING INSTALLATION. PROVIDE FULL DIAMETER BODY LAG SCREWS WITH BENDING YIELD STRENGTHS PER TABLE 12J AND 12K IN NDS.

5. PROVIDE MALLEABLE IRON WASHERS OR EQUIVALENT CUT PLATE WASHERS (NOT LESS THAN A STANDARD CUT WASHER) UNDER NUTS AND BOLT OR LAG SCREW HEADS WHICH BEAR ON WOOD.

6. WOOD SCREWS SHALL CONFORM TO ANSI/ASME STANDARD B18.6.1 AND THE REQUIREMENTS OF THE 2015 NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION BY THE NATIONAL FOREST PRODUCTS ASSOCIATION (NDS). GALVANIZED OR OTHER CORROSION RESISTANT COATING WHERE EXPOSED TO WEATHER OR USED IN FOUNDATIONS. SCREWS SHALL BE STEEL WITH CUT THREADS AND BENDING YIELD STRENGTHS PER TABLES 12L AND 12M IN NDS.

7. WOOD MEMBERS SHALL BE CUT OR NOTCHED ONLY AS SHOWN ON STRUCTURAL DRAWINGS.

8. WHEN REQUIRED NAILING TENDS TO SPLIT WOOD MEMBERS, NAIL HOLES SHALL BE PRE-BORED TO 3/4 OF THE NAIL DIAMETER.

9. STRUCTURAL NAILING SHALL BE WITH BOX NAILS PER ALL REQUIREMENTS OF 2015 NDS. NAILING NOT SPECIFICALLY INDICATED SHALL COMPLY WITH CCR TITLE 24, PART 2, TABLE 2304.9.1. ALL NAILS SHALL BE GALVANIZED OR OTHER CORROSION RESISTANT COATING WHERE EXPOSED TO WEATHER, IN FOUNDATIONS AND AS NOTED ON PLANS, PER THE REQUIREMENTS OF CCR TITLE 24, PART 2, WITH MINIMUM BENDING YIELDS PER TABLE 12N, 12P, 12Q AND 12R IN NDS. (SEE NAIL EQUIVALENC BELOW.)

10. NAIL EQUIVALENC: (PROVIDE MINIMUM NAIL LENGTHS AS REQUIRED FOR SPECIFIED PENETRATION, TYP. U.O.A.N.)
 6d EQUALS .113" DIA. - PROVIDE 1.36" MIN POINT PENETRATION
 8d EQUALS .131" DIA. - PROVIDE *1.57" MIN POINT PENETRATION
 10d EQUALS .148" DIA. - PROVIDE *1.78" MIN POINT PENETRATION
 16d EQUALS .162" DIA. - PROVIDE *1.94" MIN POINT PENETRATION
 * 1 1/2" AT 2x MEMBERS

11. PRESSURE PRESERVATIVE TREATMENT SHALL BE PER SECTION 2303.1.9, CCR TITLE 24, PART 2. PROVIDE QUALITY MARK ON ALL TREATED FOUNDATION MEMBERS. PRESSURE TREATED WOOD AND IDENTIFICATION MUST COMPLY WITH CBC 2303.1.9.1. ALL FOUNDATION MEMBERS SHALL BE MARKED AS "FOR GROUND CONTACT (UC4A)" OR "FOR ABOVE GROUND USE (UC3A OR UC3B)" AS APPROPRIATE. TREAT ALL CUT ENDS OF PRESSURE TREATED MEMBERS WITH AN APPROVED PRESERVATIVE. (WILLARD W/B COPPER GREEN 2% OR AN APPROVED EQUIVALENT) WHERE NOTED, MEMBERS BELOW THE SUB FLOOR THAT ARE NOT A PART OF THE FOUNDATION SHALL BE PRESSURE TREATED PER AWP STANDARD UI.

12. ONLY MATERIAL IN CONTACT WITH GROUND NEEDS TO BE PRESSURE TREATED. ALL OTHER FOUNDATION LUMBER CAN BE DF OR HF#2 OR EQUAL.

13. IF MACHINE NAILING IS UTILIZED FOR THIS PROJECT, CONTRACTOR SHALL COMPLY WITH ALL REQUIREMENTS OF CCR TITLE 24, PART 2. MACHINE NAILING IS SUBJECT TO APPROVAL BY THE STRUCTURAL ENGINEER OR ARCHITECT AND THE DIVISION OF THE STATE ARCHITECT.

14. FASTENERS FOR PRESSURE-PRESERVATIVE TREATED AND FIRE-RETARDANT TREATED WOOD SHALL COMPLY WITH SEC. 2304.10 OF CBC.

15. NAILS AND SPIKES USED IN WET OR EXTERIOR LOCATIONS SHALL COMPLY WITH SEC. 2304.10.5.1 OF CBC.

16. SHIM MATERIAL SHALL BE PLYWOOD CD EXP 1 OR EQUAL (NOT P.T.).

17. USED LUMBER IN GOOD CONDITION IS ACCEPTABLE FOR USE IN FOUNDATION SYSTEM.

SITE INSTALLATION REQUIREMENTS CLAUSE:

SITE INSTALLATION REQUIREMENTS FOR DSA CLASSROOM BUILDINGS. IN THE CASE OF EQUIPMENT LOCATED IN THE STATE OF CALIFORNIA, THE LESSEE IS RESPONSIBLE FOR THE SITE BEING CLEARED (FREE OF GRASS, SHRUBS, TREES, ETC.) AND GRADED TO WITHIN 4 1/2" OF LEVEL GRADE FOR EACH BUILDING. IF THE SITE EXCEEDS THE 4 1/2" REQUIREMENT ADDITIONAL COSTS MAY BE CHARGED TO LESSEE. UNDER NO CIRCUMSTANCES SHOULD THE SITE BE GREATER THAN 9" FROM LEVEL GRADE OR HAVE LESS THAN A 1000 PSF MINIMUM SOIL BEARING PRESSURE. PRIOR TO DELIVERY, THE LESSEE SHALL MARK THE FOUR CORNERS OF THE BUILDING ON THE SITE, INCLUDING THE DOOR LOCATION. SHOULD SPECIAL HANDLING BE REQUIRED TO EITHER PLACE, INSTALL OR REMOVE THE CLASSROOM ON THE LESSEE'S SITE DUE TO SITE OBSTRUCTIONS SUCH AS FENCING, LANDSCAPING, OTHER CLASSROOMS, ETC. ADDITIONAL COSTS WILL BE CHARGED TO LESSEE.

TEST AND INSPECTIONS:

1. PROVIDE ELECTRICAL GROUNDING TEST PER DSA IR E-1
2. NO OTHER TESTS AND INSPECTIONS ARE REQUIRED.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 5/17/2023



PRE-CHECK (PC) DOCUMENT
 CODE: 2019 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

MOBILE MODULAR MANAGEMENT
 11450 MISSION BLVD.
 MIRA LOMA, CA 91752

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-119396 PC
 REVIEWED FOR
 SS FLS ACS CG
 DATE: 10/29/2020

PC 04-119396
 GENERAL SPECIFICATIONS

DRAWN
 CHECKED
 DATE
 AUG. 15, 2020
 SCALE
 JOB NO.
 F-7
 OF 19 SHEETS

SITE SPECIFIC APPROVAL	DSA PC STAMP	APPROVAL - PC ENGINEER OF RECORD	MEMBER STRUCTURAL ENGINEERS ASSOCIATION OF CALIFORNIA AMERICAN CONCRETE INSTITUTE (909) 613-0234 Fax(909) 613-0238	TABLE OF CONTENTS			
				Sheet No	Description	Dated	Revised
	PRE-CHECK (PC) DOCUMENT CODE: 2019 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED	 Date Signed: September 24, 2020	 EXL STRUCTURAL ENGINEERS, INC. 4091 RIVERSIDE DRIVE, SUITE 114 CHINO, CALIFORNIA 91710				

MOBILE MODULAR MANAGEMENT PC 113193 SHEET F-7.DWG

DSA 103-19: LISTING OF STRUCTURAL TESTS & SPECIAL INSPECTIONS, 2019 CBC

Application Number: 04-119396
 School Name: Mobile Modular Management Corp
 School District: Mobile Modular Management Corp
 DSA File Number: PC-127
 Increment Number:
 Date Created: 2020-09-01 09:39:04

2019 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all facets of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc., per Title 24, Part 2, Chapter 17A (2019 CBC).

****NOTE:** Undefined section and table references found in this document are from the CBC, or California Building Code.

KEY TO COLUMNS

1. TYPE	2. PERFORMED BY
Continuous – Indicates that a continuous special inspection is required	GE – Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative. LOR – Indicates that the test or special inspection shall be performed by a testing laboratory accepted in the DSA Laboratory Evaluation and Acceptance (LEA) Program. See CAC Section 4-335. PI – Indicates that the special inspection may be performed by a project inspector when specifically approved by DSA. SI – Indicates that the special inspection shall be performed by an appropriately qualified/approved special inspector.
Periodic – Indicates that a periodic special inspection is required	
Test – Indicates that a test is required	

Appendix: Work Exempt from DSA Requirements for Structural Tests / Special Inspections

Application Number: 04-119396
 School Name: Mobile Modular Management Corp
 School District: Mobile Modular Management Corp
 DSA File Number: PC-127
 Increment Number:
 Date Created: 2020-09-01 09:39:04

Exempt items given in DSA IR A-22 or the 2019 CBC (including DSA amendments) and those items identified below with a check mark by the design professional are NOT subject to DSA requirements for the structural tests / special inspections noted. **Items marked as exempt shall be identified on the approved construction documents.** The project inspector shall verify all construction complies with the approved construction documents.

- SOILS:**
- 1. Deep foundations acting as a cantilever footing designed based on minimum allowable pressures per CBC Table 1806A.2 and having no geotechnical report for the following cases: A) free standing sign or scoreboard, B) cell or antenna towers and poles less than 35'-0" tall (e.g., lighting poles, flag poles, poles supporting open mesh fences, etc.), C) single-story structure with dead load less than 5 psf (e.g., open fabric shade structure), or D) covered walkway structure with an apex height less than 10'-0" above adjacent grade.
 - 2. Shallow foundations, etc. are exempt from special inspections and testing by a Geotechnical Engineer for the following cases: A) buildings without a geotechnical report and meeting the exception item #1 criteria in CBC Section 1803A.2 supported by native soil (any excavation depth) or fill soil (not exceeding 12" depth per CBC Section 1804A.6), B) soil scarification/recompaction not exceeding 12" depth, C) native or fill soil supporting exterior non-structural flatwork (e.g., sidewalks, site concrete ramps, site stairs, parking lots, driveways, etc.), D) ungraded landscaping and playground areas, or E) utility trench backfill.
- CONCRETE/MASONRY:**
- 1. Post-installed anchors for the following: A) exempt non-structural components (e.g., mechanical, electrical, plumbing equipment - see item 7 for "Welding") given in CBC Section 1617A.1.18 (which replaces ASCE 7-16, Section 13.1.4) or B) interior non-structural wall partitions meeting criteria listed in exempt item 3 for "Welding."
 - 2. Concrete batch plant inspection is not required for items given in CBC Section 1705A.3.3.2 subject to the requirements and limitations in that section.

NOTE:

THE EXAMPLE FORM DSA-103 SHOWN IS FOR ILLUSTRATION PURPOSES ONLY TO ASSIST IN THE COMPLETION OF FUTURE PROJECT-SPECIFIC FORM DSA-103.
 A FORM DSA-103 IS TO BE COMPLETED FOR EACH PROJECT APPLICATION THAT THIS PC IS BEING INCORPORATED INTO AND THE EXAMPLE FORM DSA-103 IS TO BE CROSSED OUT ON THIS DRAWING

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 01-120975 INC:
 REVIEWED FOR:
 SS FLS ACS
 DATE: 5/17/2023

PRE-CHECK (PC) DOCUMENT
 CODE: 2019 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

MOBILE MODULAR MANAGEMENT
 11450 MISSION BLVD.
 MIRA LOMA, CA 91752

Appendix: Work Exempt from DSA Requirements for Structural Tests / Special Inspections

Application Number: 04-119396
 School Name: Mobile Modular Management Corp
 School District: Mobile Modular Management Corp
 DSA File Number: PC-127
 Increment Number:
 Date Created: 2020-09-01 09:39:04

- 3. Non-bearing non-shear masonry walls may be exempt from certain DSA masonry testing and special inspection items as allowed per DSA IR 21-1.16. Refer to construction documents for specific exemptions accordingly for each applicable wall condition.
- 4. Epoxy shear dowels in site flatwork and/or other non-structural concrete.
- 5. Testing of reinforcing bars is not required for items given in CBC Section 1910A.2 subject to the requirements and limitations in that section.

- Welding:**
- 1. Solid-clad and open-mesh gates with maximum leaf span or rolling section for rolling gates of 10' and apex height less than 8'-0" above lowest adjacent grade. When located above circulation or occupied space below, these gates are not located within 1.5x gate/fence height (max 8'-0") to the edge of floor or roof.
 - 2. Handrails, guardrails, and modular or relocatable ramps associated with walking surfaces less than 30" above adjacent grade (excluding post base connections per the 'Exception' language in Section 1705A.2.1); fillet welds shall not be ground flush.
 - 3. Non-structural interior cold-formed steel framing spanning less than 15'-0", such as in interior partitions, interior soffits, etc. supporting only self weight and light-weight finishes or adhered tile, masonry, stone, or terra cotta veneer no more than 5/8" thickness and apex less than 20'-0" in height and not over an exit way. Maximum tributary load to a member shall not exceed the equivalent of that occurring from a 10'x10' opening in a 15' tall wall for a header or king stud.
 - 4. Manufactured support frames and curbs using hot rolled or cold-formed steel (i.e., light gauge) for mechanical, electrical, or plumbing equipment weighing less than 2000# (equipment only) (connections of such frames to superstructure elements using welding will require special inspection as noted in selected item(s) for sections 19, 19.1 and/or 19.2 of listing above).
 - 5. Manufactured components (e.g., Tolco, B-Line, Afcon, etc.) for mechanical, electrical, or plumbing hanger support and bracing (connections of such components to superstructure elements using welding will require special inspection as noted in selected item(s) for Sections 19, 19.1 and/or 19.2 of listing above).

Appendix: Work Exempt from DSA Requirements for Structural Tests / Special Inspections

Application Number: 04-119396
 School Name: Mobile Modular Management Corp
 School District: Mobile Modular Management Corp
 DSA File Number: PC-127
 Increment Number:
 Date Created: 2020-09-01 09:39:04

- 6. TV Brackets, projector mounts with a valid listing (see DSA IR A-5) and recreational equipment (e.g., playground structures, basketball backstops, etc.) (connections of such elements to superstructure elements using welding will require special inspection as noted in selected item(s) for section 19, 19.1 and/or 19.2 located in the Steel/Aluminum category).
- 7. Any support for exempt non-structural components given in CBC Section 1617A.1.18 (which replaces ASCE 7-16, Section 13.1.4) meeting the following: A) when supported on a floor/roof, $480\#$ and resulting composite center of mass (including component's center of mass) $\leq 4'$ above supporting floor/roof, B) when hung from a wall or roof/roof, $20\#$ for discrete units or $5\#$ for distributed systems.


DSA 103-19: LISTING OF STRUCTURAL TESTS & SPECIAL INSPECTIONS (SIGNATURE), 2019 CBC

Application Number: 04-119396
 School Name: Mobile Modular Management Corp
 School District: Mobile Modular Management Corp
 DSA File Number: PC-127
 Increment Number:
 Date Created: 2020-09-01 09:39:04

Name of Architect or Engineer in general responsible charge:
 Name of Structural Engineer (When structural design has been delegated):
 Signature of Architect or Structural Engineer: _____ Date: _____

Note: To facilitate DSA electronic mark-ups and identification stamp application, DSA recommends against using secured electronic or digital signatures.

DSA STAMP



IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-119396-PC
 REVIEWED FOR:
 SS FLS ACS CG
 DATE: 10/29/2020

PC 04-119396
 DSA FORM 103

SITE SPECIFIC APPROVAL	DSA PC STAMP	APPROVAL – PC ENGINEER OF RECORD	MEMBER	TABLE OF CONTENTS			
	PRE-CHECK (PC) DOCUMENT CODE: 2019 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED		STRUCTURAL ENGINEERS ASSOCIATION OF CALIFORNIA AMERICAN CONCRETE INSTITUTE (909) 613-0234 Fax(909) 613-0238	Sheet No	Description	Dated	Revised
		Date Signed: September 24, 2020	4091 RIVERSIDE DRIVE, SUITE 114 CHINO, CALIFORNIA 91710				
			This drawing and the material contained therein are the property of Mobile Modular Management Corporation (MMC) and shall not be reproduced, copied or otherwise disposed of directly or indirectly and shall not be used in whole or in part to assist in the making of, or for the purpose of furnishing, any information for the making of drawings, prints, apparatus or parts thereof without the full knowledge and written consent of MMC and all patentable material contained herein and originating with MMC and shall be the property of MMC.				

DRAWN
 CHECKED
 DATE: AUG. 15, 2020
 SCALE
 JOB NO.
 F-7A
 OF 19 SHEETS